

LTP5901 MTBF Estimation

1.0 Methods

The following calculations are made in accordance with Telecordia SR-332 Issue 3, Method 1, Case 3. The environment used was GB, GC - Ground Benign, Controlled at +25°C. No temperature rise above ambient is assumed for any part; however, given a maximum average power consumption of less than 4mW any rise above ambient will not be significant. For portions of the circuitry external to the LTC5800 which are duty cycled between different bias points the operational duty cycle is approximated at 20%. In practice these duty cycles will be significantly lower than 20%. The LTC5800, especially when operating as a mote, has the majority of the design operating either at a reduced bias or completely powered down for the vast majority of the time. Even though only a small fraction of the LTC5800 is biased 100% of the time, the LTC5800 FIT value is based upon 100% duty cycle and therefore conservative.

2.0 Calculations

Item	Quantity	Reference	Value	Part Number	Load		Rated Temp (°C)	FIT @25°C (per 10e9 H)	FIT Total @25°C (per 10e9 H)
					Rating	Actual			
1	1	R14	RES, 0, 1/16W, 5%, 0603	Yageo RC0603JR-070RL	0.0625	0.000	125	0.003	0.003
2	2	C22,C28	CAP, 1.0pF ±0.1pF, 0201, C0G	Murata GRM0335C1E1R0BD01D	6.3	0.115	125	0.990	1.980
3	10	C7,C8,C9,C10,C11,C12,C17,C18,C19,C20	Cap, 56nF, 6.3V, +/-10%, 0402 SMD	Kemet C0402C563K9RACTU	6.3	1.080	125	2.730	27.300
4	1	C21	CAP, 0.22uF, 6.3V, 10%, X7R, 0402	Taiyo Yuden JMK105B7224KV-F	6.3	0.420	125	3.030	3.030
5	2	C6,C16	CAP, CER, .1uF, 16V, A±10%, X7R, 0402	Murata GRM155R71C104KA88D	16	3.760	125	3.940	7.880
6	1	C23	CAP 2.2uF 10% 10V X7R 0603 Ceramic Chip Capacitor	Murata GRM188R71A225KE15D	10	3.760	125	4.030	4.030
7	1	C13	CAP, 0.47uF, 10V, +/-10%, 0603, X7R	TDK C1608X7R1A474K	10	0.300	125	3.240	3.240
8	1	L1	INDUCTOR, 2.2uH, 120MA, 0603	Murata LQM18FN2R2M00D	0.120	0.001	125	15.323	15.323
9	1	L5	INDUCTOR, 3.3 nH, 0201	Coilcraft 0201DS-3N3XJLW	0.63	0.002	125	0.403	0.403
10	1	X1	CRYSTAL, 32.768kHz, 8x3.8mm SMD	ECS Inc. ECS-.327-12.5-17X-TR			85	1.650	1.650
11	1	X5	CRYSTAL, 20.000MHZ, 10PF, +/-30PPM	ECS Inc. ECS-200-CDX-0914			85	1.650	1.650
12	1	ANT1	ANTENNA, 2.4 GHz, 1dbi, SMD	Fractus FR05-S1-N-0-102			85	1.000	1.000
13	1	SH1	RF SHIELD, RUSSIAN	Fotofab Dust Networks 440-0045			125	0.100	0.100
14	1	U1	QFN-72, IC	Linear Technology LTC5800			105	11.800	11.800
Total FIT (In failures per billion hours):									79.389
MTBF (Hours):									1.26E+07

3.0 Results

The FIT value for the LTP5901 is estimated to be approximately 79 and the corresponding MTBF is approximately 12,500,000 hours.