NOTES (UNLESS OTHERWISE SPECIFIED):

1. ASSEMBLE AND INSPECT IN ACCORDANCE WITH IPC STANDARD IPC-H-610D CLASS 2.
2. MAXIMUM PROTRUSION OF THE MOUSE BITES IS +0.010".
3. FINISHED ASSEMBLY TO BE FREE OF ALL SOLDER FLUX RESIDUES.
4. FINISHED ASSEMBLY TO BE SHIPPED IN APPROVED ANTI-STATIC PACKAGING.
5. ALL PROCEDURES REQUIRE ROHS-6. NO CLEAN SOLDER.
6. INSTALL RF SHIELD ON THE TOP SIDE BY INSERTING PINS INTO THE CORRECT MOUNTING HOLE POSITIONS.
   a) SOLDER ALL FOUR CORNERS ON THE TOP SIDE.
   b) CLEAN ALL FLUX RESIDUE FROM SOLDERED AREAS.
7. PLACE LABEL ON TOP OF THE SHIELD. FORMAT:
   a) DUST PART NUMBER/REV.
   b) U1 LOT NUMBER.
   c) DATE OF MANUFACTURE (WW-YY).
8. REMOVE "KEY" PIN (BOTTOM) AND TAIL (TOP) AT CONNECTOR P1
9. SHORTEN "PGOOD" PIN (BOTTOM) AT CONNECTOR P1 BY 2MM MAX (+0, -0.5 MM)
10. PLACE ISOLATION SHRINK TUBING OVER "V+" TAILS AT CONNECTORS P1 & P3 (TOP SIDE)

REVISIONS				
ECO	REV	DESCRIPTION	DATE	APPROVED
1107	1	INITIAL RELEASE	3-08-12	
1120	2	MINOR CHANGES	4-22-12	





9

		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES:	APPROVALS	DATE	SEE SEPARATE BOM, 700-0167
		TOLERANCES ARE: FRACTIONS: DECIMALS: .XX ± .01 ANGLES: 0° 30" .XXX ± .005	DRAWN BY: R.P.D.	3-08-12	DUST NETWORKS
			CHECKED		TITLE: PCA ASSY, MODULE, FRAZER
			ENGRG		
		MATERIAL –	ISSUED		B | FSCM NO. | DWG NO. 705-0185 | REV. 2
		FINISH –	CONTRACT NO.		SCALE: NONE | SHEET 1 OF 1
NEXT ASSY	USED ON	DO NOT SCALE DRAWING			
APPLICATION					