

Item Number:	9100-4445
Description:	Transformer 100/120/200/240V 47-440 Hz 2

Parametric Data		Back to Top
Functional / Physical Information	Values	Units
Body Housing Shield	SHIELDED	
Body Shield		
Create Date	2013-09-20	
DC Full Load Current #1	225	mA
DC Full Load Current #2	360	mA
DC Full Load Current #3		A
DC Full Load Current #4		A
DC Full Load Current #5		A
DC Full Load Voltage #1	18.1	V
DC Full Load Voltage #2	7.75	V
DC Full Load Voltage #3		V
DC Full Load Voltage #4		V
DC Full Load Voltage #5		V
MSL Rating		
Maximum Height - English		in
Maximum Height - Metric	52	mm
Maximum Length - English		in
Maximum Length - Metric	68.5	mm
Maximum Width - English		in
Maximum Width - Metric	57	mm

Mounting Technology		
Number Of Secondaries	2	
Operating Frequency	47-440 Hz	
Other Agencies		
Package Designation		
Package Orientation		
Primary Voltage	100/120/200/240V	
RMS Full Load Current #1		A
RMS Full Load Current #2		A
RMS Full Load Current #3		A
RMS Full Load Current #4		A
RMS Full Load Current #5		A
RMS Full Load Voltage #1		V
RMS Full Load Voltage #2		V
RMS Full Load Voltage #3		V
RMS Full Load Voltage #4		V
RMS Full Load Voltage #5		V
Tapped Secondary #1	YES	
Tapped Secondary #2	YES	

Tapped Secondary #3		
Tapped Secondary #4		
Tapped Secondary #5		
Type		
Update Date	2014-09-24	
Volt-Ampere Size Classification	LESS THAN 40 VA	