



ESA Measurement Personality Software and Firmware

The table below list all of the ESA-E Series spectrum analyzer measurement personalities. Each of the measurement personalities has a link to the latest version of software. In order to run the measurement personality, a minimum firmware is required based on that specific software. Be sure to refer to this list whenever you intend on updating any of your instrument software.

ESA Firmware Revisions		
Option	Firmware	Latest Revision
UE2	ESA Firmware	A.14.06

ESA Software Application Revisions			
Option	Software	Latest Version	Minimum Firmware
None	PowerSuite Utility	A.06.05	A.12.00
219	Noise Figure	A.01.07	A.12.00



ESA Software Application Revisions			
Option	Software	Latest Version	Minimum Firmware
225	Cable Fault Location	B.01.04	A.07.01
226	Phase Noise Utility	B.01.31	A.08.02
227	Cable TV	A.02.08	A.07.06
228	Bluetooth™	A.02.06	A.09.00
229	Modulation Analysis	A.02.02	A.08.04
231	ESA to 89601A Software Link	A.02.00	A.08.04
252	EDGE Option to GSM/GPRS	C.01.02	A.14.01
266	8566/68B Programming Compatibility	A.02.11	A.14.00
290	8590-Series Programming Compatibility	A.01.00	A.07.00
BAC	cdmaOne	A.02.03	A.07.02
BAH	GSM/GPRS	C.01.02	A.14.01
J35	FM Deviation	B.01.02	A.07.05
J36	Flexible FM Deviation	A.01.01	A.09.00

DISCOVER

Products + Services

Solutions

Industries

Events

Keysight University

SUPPORT

Keysight Product Support

EXPLORE

Success Stories

Resources

Blog

Community

PARTNERS**ABOUT KEYSIGHT**

Newsroom



[Ixia Product Support](#)

[Manage Software Licenses](#)

[Product Order Status](#)

[Parts](#)

[Investor Relations](#)

[Corporate Social Responsibility](#)

[Diversity, Equity, and Inclusion](#)

[Modern Slavery Act Transparency Statement](#)

[Careers](#)



© Keysight Technologies 2000–2021 | [Privacy](#) | [Terms](#) | [Feedback](#)

