

Avionics

ATC-600A Portable Transponder/DME Test Set

AEROFLEX
A passion for performance.



A portable transponder/DME ramp test set, the rugged ATC-600A is the ideal solution for both ramp or bench use.

- Read XPDR code and altitude numerically
- Measure transponder frequency and check for correct DME channel
- Measure transponder receiver sensitivity
- Performs all tests required by the revised Federal Aviation Regulations (91.177 and 43 Appendix F)
- Two-year limited warranty

Aeroflex is a leader in the design, manufacture and marketing of Avionics test systems.

A portable transponder/DME ramp test set, the rugged ATC-600A is the ideal solution for both ramp or bench use. Providing simulation of the ground station or airborne environment, the ATC-600A meets the latest ARINC specifications and FAA regulations concerning transponder receiver sensitivity and SLS tests.

Transponder tests allow quick determination of transmitter power, frequency, percent reply, pilot's code and encoded altitude. For DME testing, the unit includes accurate range and velocity simulation, power and frequency and PRF measurements.

Performance Features

The ATC-600A will perform, with radiated signals, all the tests required by the revised Federal Aviation Regulations (91.177 and 43 Appendix F, as amended December 19, 1973).

- Reads out XPDR code and altitude numerically and also displays binary pulse information for code and altitude
- Measures transponder frequency and checks for correct DME channel
- Front panel connector provided to directly check the output of altitude encoders
- Capable of checking XPDR input pulse decoder gate for marginal operation
- Checks position of XPDR second framing pulse relative to F₁
- Measures transponder receiver sensitivity and SLS tests
- Precision DME range and velocity signals, both X and Y channel
- Uses remote tripod mounted antenna - can be accurately spaced from aircraft antenna for power measurements

SPECIFICATION

TRANSPONDER

Interrogations Output

Frequency

1030 MHz ($\pm 0.006\%$)

Level

Variable from -66 to -79 dBm (± 1.5 dBm) with 34 dB pad or radiat-

For the very latest specifications visit www.aeroflex.com

ed with properly spaced antenna

Modes

A/C, Altitude or Pilot Code, 2:1 interlace, or Mode A
(Mode B available on request)

Pulse Spacing

Mode A	P_1 to P_3	8 μ s (± 0.1 μ s)
Mode C	P_1 to P_3	21 μ s (± 0.1 μ s) (In A/C Modes)
Mode C	P_1 to P_3	17 μ s (± 0.1 μ s)
SLS	P_1 to P_2	± 0.1 μ s

Variable Spacing

P_2 and P_3 variable with respect to P_1 (± 1 μ s), ± 1 μ s from nominal for input decoder gate tests

PRF

235 Hz ($\pm 10\%$)

SLS Test

± 1.0 dB P_2 inserted at 0 or -9 dB relative to P_1

REPLY MEASUREMENTS

Power (UUT)

10 W to 1.5 kW peak ($\pm 20\%$); direct with 34 dB pad
 ± 3 dB radiated with properly spaced antenna

Frequency Check

1086 to 1093 MHz (± 0.3 MHz)

Altitude Code

Binary and Numerical Readout, -1.0 to 126.7 thousand feet

Pilot Code

Binary and Numerical Readout, 0000 to 7777

Percent Reply

0% to 100%, either A/C or A(B) modes

F₂ Pulse Position

Measurement of rising and falling edge ± 0.5 μ s from nominal (± 0.05 μ s)

Status Lamps

Ident Pulses, Invalid Altitude Code and No Altitude Code

Encoder Test

Direct connection accepts altitude encoder

DME

Interrogations Measurements

PRF

Track PRF	0 to 30 Hz	$\pm 5\%$ full scale
Search PRF	0 to 300 Hz	$\pm 5\%$ full scale

Power (UUT)

10 W to 1.5 kW peak ($\pm 20\%$); direct with 34 dB pad
 ± 3 dB radiated with properly spaced antenna

Frequency Check

1038 to 1045 MHz (± 0.3 MHz)

Reply Output

Frequency

17X-channel:	978 MHz	$\pm 0.006\%$ (108.00 MHz paired)
17Y-channel:	1104 MHz	$\pm 0.006\%$ (108.05 MHz paired)
18X-channel:	979 MHz	$\pm 0.006\%$ (108.10 MHz paired)

Level

Approximately -45 direct with 34 dB pad or radiated with properly spaced antenna

Reply Pulses

3.5 μ s wide (± 0.5 μ s)

Pulse Spacing

X channel: 12 μ s wide (± 0.2 μ s)
Y channel: 30 μ s wide (± 0.2 μ s)

Range

0 to 399 NM in 1 NM steps. Accuracy ± 0.07 NM ($\pm 0.02\%$)

Velocity

Crystal-controlled digital velocity with rates of 50, 75, 100, 150, 200, 300, 400, 600, 800, 1200, 1600 and 2400 knots ($\pm 0.02\%$ of setting). Inbound or outbound starting from any selected range. Range steps in velocity mode are 0.025 NM (system), 0.1 NM displayed.

Percent Reply

50% or 100%

Squitter

2700 PRF (± 50 Hz)

Ident Tone

1350 Hz (± 8 Hz) with equalizing pulses

GENERAL

ENVIRONMENTAL

Temperature

-20° to 55°C

Relative Humidity

$\leq 80\%$ for temperature up to 31°C, decreasing linearly to 50% at 40°C (Non-condensing)

Altitude

≤ 4000 meters (13,124 feet)

GENERAL

Calibration Interval

1 year

Power

102 to 120 VAC, 220 to 240 VAC, 50 Hz to 400 Hz, $\leq \pm 10\%$ of the nominal voltage, 24 W maximum

Internal 2.0 AH NICAD battery operation for approximately 2 hours

DIMENSIONS

Housed in a portable case 290 mm wide, 130 mm high, 410 mm deep

Housed in a portable case 11.4 in. wide, 5.1 in. high, 16.1 in. deep

Weight

8.1 kg (18 lbs.) approximately

Electromagnetic Compatibility

Complies with the limits in the following standards:

EN 55011 Class B

EN 50082-1

Safety

Complies with EN 61010-1 for class 1 portable equipment and is for use in a pollution degree 2 environment. The instrument is designed to operate from an installation category 1 or 2 supply.

VERSIONS AND ACCESSORIES

When ordering please quote the full ordering number information.

Ordering Numbers

Versions

600-110	ATC-600A	Transponder/DME Equipment, 110 VAC operation	Ramp	Test
600-220	ATC-600A	Transponder/DME Equipment, 220 VAC operation	Ramp	Test

All Aeroflex Avionics products delivered with Factory Certificate Of Calibration

CHINA

Tel: [+86] (21) 6282 8001
Fax: [+86] (21) 6282 8002

EUROPE

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UNITED KINGDOM

Tel: [+44] (0) 1438 742200
Toll Free: [+44] (0800) 282 388 (UK only)
Fax: [+44] (0) 1438 727601

USA

Tel: [+1] (316) 522 4981
Toll Free: [+1] (800) 835 2352 (US only)
Fax: [+1] (316) 522 1360



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2003.

www.aeroflex.com
info-test@aeroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.

Part No. 46891/031, Issue 3, 10/03