

APPENDIX F - SPECIFICATIONS

SIGNAL GENERATOR

Output Frequency:	1030 MHz (± 10 kHz), DCXO controlled
Level:	-57 to -7 dBm typically, into 50 Ω (Automatically controlled to determine receiver sensitivity [MTL] for the selected range and 4 dB typically, higher than MTL for test interrogations)
Test Antenna:	Remote antenna VSWR <1.5:1
Gain:	10 dB typically, specified on the antenna
Range:	6 feet (1.83 meters) to 300 feet (91.44 meters)

TEST SIGNALS (INTERROGATIONS)

Rate: 235 Hz PRF (± 5 Hz)

Interlace Ratio (MTL Interrogations to Test Interrogations):

 ATCRBS: 2:1

 Mode S: 8:1

Modes: A, C, S, Intermode

NOTE: The ATC-601-2 interrogates with the mode(s) necessary to run the selected test.

PULSE CHARACTERISTICS (MEASURED AT 50% AMPLITUDE POINTS)

Spacing:

Mode A:

 P1 to P2: 2.00 μ s (± 50 ns)

 P1 to P3: 8.00 μ s (± 50 ns)

Mode C:

 P1 to P2: 2.00 μ s (± 50 ns)

 P1 to P3: 21.00 μ s (± 50 ns)

Mode S:

 P1 to P2: 2.00 μ s (± 50 ns)

 P1 to P6: 3.50 μ s (± 50 ns)

 P1 to SPR: 4.75 μ s (± 50 ns)

Intermode:

Mode A:

 P1 to P3: 8.00 μ s (± 50 ns)

 P1 to P4: 10.00 μ s (± 50 ns)

Mode C:

 P1 to P3: 21.00 μ s (± 50 ns)

 P1 to P4: 23.00 μ s (± 50 ns)

Widths:

Mode A:

P₁, P₂, P₃: 0.80 μs (±50 ns)

Mode C:

P₁, P₂, P₃: 0.80 μs (±50 ns)

Mode S:

P₁, P₂: 0.80 μs (±50 ns)

P₆ (Short): 16.25 μs (±50 ns)

P₆ (Long): 30.25 μs (±50 ns)

Intermode:

P₁, P₂, P₃: 0.80 μs (±50 ns)

P₄ (Short): 0.80 μs (±50 ns)

P₄ (Long): 1.60 μs (±50 ns)

Rise and Fall Times:

Rise Time (all modes): 50 to 100 ns

Fall Time (all modes): 50 to 200 ns

Phase Modulation:

Transition Time: ≤80 ns

Phase Shift: 180° (±10°)

Amplitude Levels:

SLS Level (P₂): -9 dB (±1 dB) and 0 dB relative to P₁ level

NOTE: SLS Level is automatically controlled in the SLS LEVEL Test.

UUT MEASUREMENTS (REPLIES)

XMTR Frequency:

Range:	1087 to 1093 MHz
Accuracy:	±50 kHz
Resolution:	10 kHz

XMTR Power (at 1090 MHz):

**Direct Connection-Peak
Pulse Power:**

Range:	+46.5 to +59 dBm (45 to 800 W)
Accuracy:	±1 dB
Resolution:	0.1 dB

Effective Radiated Power (ERP):

Range:	+48.5 to +57 dBm (71 to 500 W)
--------	--------------------------------

Receiver Sensitivity:

**Direct Connection - Minimum
Triggering Level (MTL):**

Range:	-67 to -79 dBm
Accuracy:	±2 dB

Radiated Field Strength (MTL):

Range:	-69 to -77 dBm into 0 dBi antenna (-77 dB W/m ² to -85 dB W/m ²)
--------	--

Reply Delay:

ATCRBS:

Range:	1.80 to 7.00 µs
Accuracy:	±100 ns

**Mode S and ATCRBS/Mode S
All-Call:**

Range:	125.00 to 131.00 µs
Accuracy:	±100 ns

Reply Jitter:

ATCRBS:

Range:	0.00 to 2.30 µs
Accuracy:	±50 ns

**Mode S and ATCRBS/Mode S
All-Call:**

Range:	0.00 to 6.00
Accuracy:	±50 ns

F₁ to F₂ Spacing:

Range: 19.70 to 21.60 μ s
Accuracy: \pm 50 ns

F₁ and F₂ Pulse Width:

Range: 0.25 to 1.00 μ s
Accuracy: \pm 50 ns

Squitter Period:

Range: 0.10 to 4.88 seconds
Accuracy: \pm 10 ms

Diversity Isolation:

Range: 0 to >20 dB (depending on Antenna Range)
Antenna Range: 6 feet (1.83 meters) to 50 feet (15.24 meters)
Accuracy: \pm 3 dB

SLS Test (at MTL + 10 dB):

Antenna Range: 6 feet (1.83 meters) to 95 feet (28.96 meters)

BATTERY OPERATION

Duration: \geq 2 hours before recharge at 25°C
Automatic shutoff: After 15 minutes of non-use

AC POWER

Source Voltage and Frequency: 100 to 120 VAC, 60 Hz
220 to 240 VAC, 50 Hz
Power Consumption: 37 W Maximum
30 W Nominal at 115 VAC
22 W Nominal at 230 VAC
Nominal Input Current: 0.36 A at 115 VAC
0.18 A at 230 VAC
Main Supply Voltage Fluctuations: \leq \pm 10% of the nominal voltage
Transient Overvoltages: According to Installation Category II

FUSE REQUIREMENTS

F1 and F2:
100 to 120 VAC: 1.0 A, 250 V, Type F
220 to 240 VAC: 0.5 A, 250 V, Type F

ENVIRONMENTAL

Use: Pollution Degree 2
Altitude: \leq 13,124 feet (4000 meters)
Temperature: 5°C to 40°C (41°F to 104°F)
Relative Humidity: \leq 80% for temperatures up to 31°C,
decreasing linearly to 50% at 40