

Avionics

PSD60-2R Fuel Quantity Test Set



AEROFLEX
A passion for performance.

A fuel tester that makes a powerful difference in line and hangar maintenance

The PSD60-2R performs these functions:

- Measurement of total tank capacitance, individual tank units and compensators
- Simulation of capacitance for indicator calibration
- Simulation of compensator capacitance value for dry calibration
- Measurement of the insulation resistance of tank units and aircraft harness
- Measurement of coax center conductor to shield for fault isolation
- Display of capacitance resolution to 0.00 pF for accurate individual tank unit testing (to 199.99 pF)
- Compatible with AD 98-20-40 & AD 99-03-04 compliant aircraft (Mod 6 and above)
- Modular design for high reliability and low maintenance
- Closed box calibration using front panel controls - performed annually
- Battery powered with percent of charge displayed
- Maintenance codes displayed to aid in troubleshooting
- Distance-to-Fault (DTF) Mode determines the "length" of the wire or the approximate distance to a break in the wire or shield
- Large selection of aircraft specific interface cables readily available

The PSD60-2R is an accurate, highly reliable, portable capacitance test set. Along with an aircraft specific interface, the PSD60-2R will test any AC Capacitive Fuel, Water, LOX, Engine Oil, or other AC capacitance system

GENERAL SPECIFICATIONS

MEASUREMENT RANGE

Capacitance

0.00 to 19,999 pF in 3 ranges

Resistance

0.00 Ω to 1,999 M Ω in 8 ranges

Optional range: 2,000 to 19,999 M Ω

MEASUREMENT ACCURACY

Capacitance

$\pm 0.1\%$ of reading or 0.05 pF, whichever is greater, from -25° to $+55^\circ$ C

Resistance

$\pm 2\%$ of reading or 0.1 Ω , whichever is greater, from -25° to $+55^\circ$ C;
 $+ 5\%$ in Range 9 (2,000 M Ω to 19,999 M Ω)

CAPACITANCE SIMULATOR RANGE

Tank Unit

10 - 9,990 pF with infinite resolution

Compensator

10 - 990 pF with infinite resolution

PHYSICAL CHARACTERISTICS

Weight

12 lbs (5.4 kg)

Width

14 in (35.6 cm)

Height

6.5 in (16.5 cm)

Depth

10.6 in (26.9 cm)

Power

18 Alkaline C-size non-rechargeable batteries, internally mounted

ORDERING INFORMATION

PSD60-2R Test Set AC Capacitance Universal Fuel Test Set

EXTENDED WARRANTY

WPSD/203C Extended standard warranty 36 months with scheduled calibration

WPSD/205C Extended standard warranty 60 months with scheduled calibration

Aircraft specific interface cables are required and must be purchased separately. Contact Aeroflex for your application.

CHINA Beijing

Tel: [+86] (10) 6467 2761 2716
Fax: [+86] (10) 6467 2821

CHINA Shanghai

Tel: [+86] (21) 6282 8001
Fax: [+86] (21) 62828 8002

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA

Tel: [+91] 80 5115 4501
Fax: [+91] 80 5115 4502

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UK Burnham

Tel: [+44] (0) 1628 604455
Fax: [+44] (0) 1628 662017

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA Wichita

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

USA New Century

Tel: [+1] (913) 764 2452
Fax: [+1] (913) 782 5104

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2006.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.