

## APPENDIX H - ABBREVIATIONS

<b>A</b>		<b>F</b>	
AC	Alternating Current	FCC	Federal Communications Commission
ac	Alternating Current	FM	Frequency Modulated
ADF	Automatic Direction Finder	FREQ	Frequency
ADJ	Adjustment	Ft	Feet
AFC	Automatic Frequency Control		
AGC	Automatic Gain Control	<b>G</b>	
AM	Amplitude Modulated	GEN	Generator
AMPL	Amplifier	GHz	Gigahertz ( $10^9$ )
ANLYZER	Spectrum Analyzer	GND	Ground
ARINC	Aeronautical Radio, Inc.	<b>H</b>	
ASCII	American Standard Code for Information Interchange	H	Henry
ATE	Automatic Test Equipment	h	Hexadecimal
ATTEN	Attenuation	HET	Heterodyne
AUX	Auxiliary	HI	High
		hr	Hour
<b>B</b>		HZ	Hertz
BCD	Binary-Coded Data	<b>I</b>	
BD	Board	IEEE	Institute of Electrical and Electronic Engineers
BPF	Bandpass Filter	IF	Intermediate Frequency
		INTL	Internal
<b>C</b>		I/O	Input/Output
ccw	Counterclockwise	<b>K</b>	
CHAN	Channel	k $\Omega$	Kilo-ohm ( $10^3$ )
cm	Centimeter	kg	Kilograms ( $10^3$ )
CMOS	Complementary Metal-Oxide Semiconductor	kHz	Kilohertz ( $10^3$ )
CONT	Control	km	Kilometers ( $10^3$ )
Cont	Continued	kts	Knots (Velocity)
CW	Continuous Wave	kV	Kilovolts ( $10^3$ )
cw	Clockwise	kW	Kilowatts ( $10^3$ )
		<b>L</b>	
<b>D</b>		LED	Light Emitting Diode
D/A	Digital to Analog	LO	Local Oscillator
dB	Decibel	LPF	Low-Pass Filter
dBc	Decibels relative to carrier	LRU	Line Repairable Unit
dB <sub>i</sub>	Decibels above isotropic		
dB <sub>m</sub>	Decibels above one milliwatt		
dc	Direct Current		
DET	Detector		
Div	Division		
DLYD	Delayed		
DMM	Digital Multimeter		
DSCRM	Discriminator		
		<b>E</b>	
EFF	Effective		
EXT	External		
Ext	External		

<b>M</b>		<b>S</b>	
m	Meters	SCOPE	Oscilloscope
Max	Maximum	SCP	Oscilloscope
MDR	Minimum Detectable Range	sec	Seconds
MDS	Minimum Discernible Signal	SEL	Select
mH	Millihenry ( $10^{-3}$ )	S/N	Serial Number
MHz	Megahertz ( $10^6$ )	STC	Sensitivity Time Control
Min	Minimum	SWP	Sweep
MKR	Marker	SYNC	Synchronization
MNL	Manual		
MOD	Modulator	<b>T</b>	
MON	Monitor	TGS	Tangential Sensitivity Signal
ms	Milliseconds ( $10^{-3}$ )	TRIG	Trigger
mV	Millivolt ( $10^{-3}$ )	TTL	Transistor-Transistor Logic
		TWT	Traveling Wave Tube
<b>N</b>			
N/A	Not Applicable	<b>U</b>	
NM	Nautical Miles	UUT	Unit Under Test
nmi	Nautical Miles		
ns	Nanoseconds ( $10^{-9}$ )	<b>V</b>	
		V	Volts
<b>O</b>		VHF	Very High Frequency
OSC	Oscillator	VAC	Volts, Alternating Current
		VCO	Voltage Controlled Oscillator
<b>P</b>		Vdc	Volts, Direct Current
PC	Printed Circuit	VHF	Very High Frequency
pF	Picofarads ( $10^{-12}$ )	Vp	Volts Peak
PLCS	Places	Vp-p	Volts Peak-to-Peak
PM	Pulse Modulated	VSWR	Voltage Standing Wave Ratio
PPM	Pulse Position Modulated		
ppm	Parts per Million	<b>W</b>	
PRF	Pulse Repetition Frequency	W	Watts
psi	Pounds per Square Inch		
PWM	Pulse Width Modulated	<b>X</b>	
PWR	Power	XCVR	Transceiver
		XMTR	Transmitter
<b>R</b>		XTAL	Crystal
RCT	Rain Echo Attenuation Compensation Technique	$\Delta F$	Delta F (Frequency Change)
RCV	Receive	$\Omega$	Ohms
RCVR	Receiver	$\mu F$	Microfarads ( $10^{-6}$ )
REF	Reference	$\mu s$	Microseconds ( $10^{-6}$ )
RF	Radio Frequency		
RMS	Root Mean Square		
R/T	Receiver/Transmitter		
RTCA	Radio Technical Commission for Aeronautics		