



8000B 10 V BINARY VOLTAGE DIVIDER

Developed & designed by metrologists for metrologists & calibration technicians



Featuring

- ▶ 20-Channel Scanner
- ▶ Bipolar Voltage Measurements
- ▶ Best Accuracy <math> < 0.05 \text{ ppm} \times 10^{-6}</math>
- ▶ Linearity <math> < 0.02 \times 10^{-6}</math>
- ▶ Standard Cell Protection
- ▶ Voltage Maintenance Programs
- ▶ Range of 1200 Volts
- ▶ Calibration of Fluke 5700A/5720A
- ▶ Linearity Calibration of DMM's
- ▶ Bipolar Voltage Measurements
- ▶ Traceability to 10 V Zener Reference

Overview

The model 8000B is a highly versatile, accurate, self-balancing instrument that meets laboratory requirements for scaling between 10 Volt references or any voltage between 1 mV to 10 Volts. Automatic self-calibration ensures ratios to nine significant digits with

linearity deviations of less than 0.02 ppm. The model 8000B has a 20-channel “built-in” scanner addressed individually via the Windows operating software for performing automatic measurements. Both hardware and software standard cell protection circuits are built-in.

Feature	Benefit
Automated self-calibration.	Does not require sending out for calibration.
Bi-polar voltage measurements.	Allows for automatic + and - voltage measurements against +10 V Reference.
Built-in 20-channel scanner.	Allows for automation of multiple UUT's without connection changes to minimize thermal effects.
Standard cell protection.	Protects references against accidentally shorting or loading.
Voltage maintenance.	Ideally suited to calibrate and intercompare 10 V Zener references.
Low uncertainties.	0.05×10^{-6} for 10 V vs. 10 V measurements.



Measurements International

Metrology is Our Science, Accuracy is Our Business™

8000B 10 V BINARY VOLTAGE DIVIDER

Specifications: Rev 2

Automatic Self-Calibration	Completely Self-Checking	
Range	1 mV to 10 V (Single Continuous)	
Accuracy K=2 * We have attempted to include all reasonable considerations for our uncertainty budgets but your uncertainty budgets should be re-assessed considering your environment, operating conditions and metrological needs. As this is a ratio device, the results that we show can easily be improved upon. ** Lower Voltages, e.g. 100 mV, 10 mV, 1 mV the resolution of the DMM (Detector) becomes the dominant uncertainty.	1 mV	< 200×10^{-6}
	10 mV	< 50×10^{-6}
	100 mV	< 5×10^{-6}
	1 V	< 0.5×10^{-6}
	10 V	< 0.05×10^{-6}
Insulation Resistance	$10^{11} \Omega$	
Effective Linearity	< 0.02 ppm of Full-scale (Full-scale 1 V, 10 V)	
Long-term Drift	N/A – Corrected by Self-Calibration	
Short-term Drift	Dependant on Drift of Source and Environmental Conditions	
Input Impedance	40 k Ω	
Output Impedance	100 k Ω	
Operating Environment	18 to 34 °C, 10 to 80 % RH	
Storage Environment	-5 °C to 40 °C, 95 % Non-condensing	
Warranty	2 Years Parts & Labour	

How to Order Model 8000B - 10 V Binary Voltage Divider	Accessories 10 V Reference 1330A or 732C Detector 3458A or 2182A
--	---

Dimensions (L × W × H):
610 × 508 × 407 (mm)

Weight:
11 kg

Shipping Weight:
21 kg

Main Power:
100 V_{ac}-240 V_{ac} – 50/60 Hz
10 VA Max.

Corporate Headquarters
Measurements International
PO Box 2359, 118 Commerce Drive
Prescott, Ontario, Canada K0E 1T0

Phone: 613-925-5934
Fax: 613-925-1195
Email: sales@mintl.com
Toll Free: 1-800-324-4988

Worldwide Offices
MI-USA
Phone: 407-706-0328
Email: sales@mintl.com

MI-China
Phone: +(86) 10-64459890
Email: sales@mintl.com

MI-Europe
Phone: +(420) 731-440-663
Email: sales@mintl.com

MI-Japan
Phone: +(81) 72 39 64 660
Email: kaz@mijpn.com

MI-India
Phone: +(91) 98 10 134 932
Email: sales@MILLP.co.in

