













Serial Flash Socket Adapters











SOIC16 JEDEC

SOIC8 WIDE

DIP8

SOIC8 NAROW

WSON8

SPI Memory Socket Adapters



SOIC-16

JEDEC standard 16-lead 0.300" (7.62mm) wide, 0.05" (1.27mm) pitch.

\$15.00 Add to Cart



SOIC-8 Wide EIAJ standard 8-lead, 0.200" (5.08mm) wide, 0.05" (1.27mm) pitch.

\$15.00 Add to Cart



SOIC-8 Narrow JEDEC standard 8-lead 0.150" (3.81mm) narrow, 0.05" (1.27mm) pitch.

\$15.00 Add to Cart



TSSOP-8

Compatible with SPI devices in TSSOP-8 package (3mm wide) such as AT25DF041B.

\$15.00 Add to Cart



WSON-8

DFN-8 / MLP-8 JEDEC package (Size: 8x6 mm)

\$58.00 Add to Cart

WSON-8 DFN-8 / MLP-8 JEDEC package

(Size: 6x5 mm)

\$58.00 Add to Cart





USON-8 package USON-8 (Size: 2x3 mm)

\$58.00 Add to Cart



BGA-24 FAB024

BGA-24 socket for 5 x 5 ball (FAB024). SPI and SQI only; HyperFlash requires parallel socket.

\$125.00 Add to Cart



BGA-24

FAC024

BGA-24 socket for 4 x b ball (FAC024).



\$125.00 Add to Cart

Microwire and AT45 Socket Adapters



SOIC-8 Narrow

Microwire compatible variant (93 series)

JEDEC standard 8-lead 0.150" (3.81mm) narrow, 0.05" (1.27mm) pitch.

\$15.00 Add to Cart



SOIC-8 Wide

ATMEL / Adesto AT45 Series compatiblevariant

EIAJ standard 8-lead, 0.200" (5.08mm) wide, 0.05" (1.27mm) pitch.

\$15.00 Add to Cart



SOIC-8 Narrow

ATMEL / Adesto AT45 Series compatible variant

\$15.00

JEDEC standard 8-lead 0.150" (3.81mm) narrow, 0.05" (1.27mm) pitch.

Add to Cart

I2C Memory Socket Adapters

Standard 8-lead, 0.10" (2.54mm) pitch. Compatible DIP-8 with SPI Flash and I2C EEPROM devices.

\$10.00

Add to Cart





SOIC-8 Narrow

Compatible with I2C EEPROM devices in SO8 JEDEC package (0.150" wide).

\$15.00 Add to Cart



SOIC-8 Wide

Compatible with I2C EEPROM devices in SO8 EIAJ package (0.200" wide). This variant is rare.

\$15.00 Add to Cart



TSSOP-8

Compatible with I2C serial EEPROM devices in TSSOP8 package (169 mil width)

\$15.00 Add to Cart

Single-wire



SOT-23 and SOIC-8

Compatible with 1-wire EEPROM devices such as AT21CS01/AT21CS11. This combo socket includes both SOT-23 and SOIC-8 JEDEC packages.

\$28.00 Add to Cart

SPI Sockets for FlashcatUSB MACH¹



IDC-10

Allows MACH¹ to use any of the above SPI socket adapters or SPI programming cables. Note: MACH¹ does not support I2C, Microwire or 1-Wire protocol.

\$1.00 Add to Cart

STI ACAPATICA

SOIC-16 MACH1 SOIC-16 JEDEC adapter for SPI Flash devices that connects to the MACH¹ programmer. Note: this is not compatible with XPORT. [Pinout]

\$16.00 Add to Cart

SOIC-8 MACH1 SOIC-8 adapaters in both wide and narrow packages for the MACH¹ programmer. This adapter is for standard SPI Flash Devices (25 and 26 series), it is not compatible with the Adesto AT45 series. [Pinout]

\$30.00 Add to Cart



Copyright 2022 - All content is property of Embedded Computers LLC