

SAFETY DATA SHEET

Revision: 2.0 Date: 22.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name M-Line 570-28R Solder
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.
- 1.2 Recommended use of the chemical and restrictions on use**
Identified Use(s) PC38 Welding and soldering products (with flux coatings or flux cores.), flux products
Uses Advised Against For professional users only.
- 1.3 Supplier's details**
Company Identification VISHAY MEASUREMENTS GROUP, INC.
Post Office Box 27777
Raleigh, NC 27611
USA
Telephone 919-365-3800
Fax 919-365-3945
E-Mail (competent person) mm.us@vishaypg.com
- 1.4 Emergency Phone No.** 1-800-424-9300
CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
- 2.1.1 GHS Classification** Skin Sens. 1; H317
Repr. 1A; H360DF
Lact.; H362
- 2.2 Label elements**
Product Name M-Line 570-28R Solder
Hazard Pictogram(s) 
- Signal Word(s) Danger
- Contains: Lead and Rosin reacted product
- Hazard Statement(s) H317: May cause an allergic skin reaction.
H360FD: May damage fertility. May damage the unborn child.
H362: May cause harm to breast-fed children.
- Precautionary Statement(s) P201: Obtain special instructions before use.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P363: Wash contaminated clothing before reuse.
P308+P313: IF exposed or concerned: Get medical advice/attention.
- Additional Information** None.

SAFETY DATA SHEET

Revision: 2.0 Date: 22.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

2.3 Other hazards

Contact with flux or fumes may cause local irritation.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

GHS Classification

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Lead	60-100	7439-92-1	231-100-4	None assigned	Repr. 1A; H360DF Lact.; H362
Rosin reacted product	1-5	-	-	None assigned	Skin Sens. 1; H317

H317: May cause an allergic skin reaction. H360FD: May damage fertility. May damage the unborn child. H362: May cause harm to breast-fed children.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention.

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation develops or persists.

Ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. IF exposed or concerned: Get medical advice/attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. May damage fertility. May damage the unborn child. May cause harm to breastfed babies. Contact with flux or fumes may cause local irritation. High atmospheric concentrations may lead to adverse effects on the central nervous system and anaesthetic effects, including drowsiness, giddiness, headache, nausea and unconsciousness. Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels. Symptoms of lead poisoning include abdominal pain, nausea, vomiting and headache. May cause gastrointestinal tract irritation if swallowed. Lead poisoning may cause lassitude, weight loss, anemia, nausea, vomiting, central nervous system damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. In case of burns immediately cool affected skin as long as possible with cold water. If thought to be overexposed, the person should have a blood-lead analysis done. Patient should be kept under medical observation for at least 48 hours.

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media

As appropriate for surrounding fire. Extinguish preferably with foam, carbon dioxide or dry chemical.

Unsuitable extinguishing media

Do not use water on fires when molten metal is present.

5.2 Special hazards arising from the substance or mixture

Decomposes in a fire giving off toxic fumes: Formaldehyde. High temperatures may produce heavy metal fumes, dust and/or vapor.

SAFETY DATA SHEET

Revision: 2.0 Date: 22.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

- 5.3 Advice for fire-fighters** Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation. Use personal protective equipment as required. See Section: 8. Melted solder will solidify on cooling and can be scraped up. Avoid breathing smoke fumes during soldering. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces.
- 6.2 Environmental precautions** Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.
- 6.3 Methods and material for containment and cleaning up** Allow product to cool/solidify and pick up as a solid. Transfer to a container for disposal. Recover or recycle if possible. Dispose of this material and its container as hazardous waste.
- 6.4 Reference to other sections** See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all contact. Avoid breathing smoke fumes during soldering. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces. When molten: Keep from any possible contact with water. Ensure adequate ventilation. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
- 7.2 Conditions for safe storage, including any incompatibilities** Store in a well-ventilated place.
- Storage temperature: Ambient.
Storage life: Stable under normal conditions.
Incompatible materials: Keep away from: Strong Acids (Nitric acid), Chlorine and Strong oxidising agents. Store away from sources of sulfur.
- 7.3 Specific end use(s)** PC38 Welding and soldering products (with flux coatings or flux cores.), flux products. See Section: 1.2

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Lead and inorganic compounds (as Pb)	7439-92-1	-	0.05*	-	-	NIOSH
Lead and inorganic compounds (as Pb)	7439-92-1	-	0.05*	-	-	OSHA

Note: OSHA 1910.1000 TABLE Z-1 / NIOSH

*: Total dust

- 8.1.2 Biological limit value** Not established.
- 8.1.3 PNECs and DNELs** Not established.
- 8.2 Exposure controls**
- 8.2.1 Appropriate engineering controls** Ensure adequate ventilation. or Use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit.
- 8.2.2 Individual protection measures, such as personal** General hygiene measures for the handling of chemicals are applicable. Avoid

SAFETY DATA SHEET

Revision: 2.0 Date: 22.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

protective equipment (PPE)

all contact. Avoid breathing smoke fumes during soldering. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Eye/ face protection

When molten: Goggles or Full face shield.



Skin protection

Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.



Respiratory protection

In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.



Thermal hazards

Not applicable.

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Grey metal in wire form
Odour	Mild odour
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	296 - 565°C
Initial boiling point and boiling range	Not available.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Non-flammable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	Not available.
Vapour density	>1 (Air = 1)
Relative density	11.1 (H2O = 1)
Solubility(ies)	Insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2 Other information

Volatile Organic Compound Content: <1%

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Stability and reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides. Reacts vigorously with chlorine and oxidising agents.
10.4 Conditions to avoid	When molten: Keep from any possible contact with water.
10.5 Incompatible materials	Keep away from: Strong Acids (Nitric acid), Chlorine and Strong oxidising agents. Store away from sources of sulfur.
10.6 Hazardous decomposition product(s)	Decomposes in a fire giving off toxic fumes: Formaldehyde. High temperatures

SAFETY DATA SHEET

Revision: 2.0 Date: 22.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

may produce heavy metal fumes, dust and/or vapor.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity	
Ingestion	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
Inhalation	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20.0 mg/l.
Skin Contact	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
Skin corrosion/irritation	Based upon the available data, the classification criteria are not met.
Serious eye damage/irritation	Based upon the available data, the classification criteria are not met.
Respiratory or skin sensitization	Skin Sens. 1: May cause an allergic skin reaction.
Germ cell mutagenicity	Based upon the available data, the classification criteria are not met.
Carcinogenicity	Based upon the available data, the classification criteria are not met.
Reproductive toxicity	Repr. 1A: May damage fertility. May damage the unborn child. Lact.: May cause harm to breastfed babies.
STOT - single exposure	Based upon the available data, the classification criteria are not met.
STOT - repeated exposure	Based upon the available data, the classification criteria are not met.
Aspiration hazard	Based upon the available data, the classification criteria are not met.
11.2 Other information	None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Based upon the available data, the classification criteria are not met. Estimated Mixture LC50 >100 mg/l (Fish)
12.2 Persistence and degradability	Part of the components are poorly biodegradable.
12.3 Bioaccumulative potential	The product has low potential for bioaccumulation. (Metal in wire form)
12.4 Mobility in soil	The product is predicted to have low mobility in soil. (Metal in wire form)
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Other adverse effects	None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	Solder can be reclaimed. Dispose of this material and its container as hazardous waste.
13.2 Additional Information	Dispose of contents in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

	ADR/RID / IMDG / IATA
14.1 UN number	Not classified as dangerous for transport.
14.2 Proper Shipping Name	Not classified
14.3 Transport hazard class(es)	Not classified
14.4 Packing group	Not classified
14.5 Environmental hazards	Not classified as a Marine Pollutant.
14.6 Special precautions for user	See Section: 2
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
14.8 Additional Information	None.

SAFETY DATA SHEET

Revision: 2.0 Date: 22.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.2 National regulations
USA

NTP: Lead (CAS# 7439-92-1): Reasonably anticipated to be a human carcinogen .

IARC Monographs: Lead (CAS# 7439-92-1): Group 2B (Possibly carcinogen to humans).

OSHA Regulated: Not listed

15.1.1 EU regulations

Authorisations and/or Restrictions On Use

Lead concentrations in electrical equipment are controlled by Directive 2002/95/EC (commonly referred to as the Restriction of Hazardous Substances Directive or RoHS) and recast Directive 2011/65/EU.

SVHCs

None

Germany

Water hazard class: 3

15.2 Chemical Safety Assessment

Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS) and the Committee for Risk Assessment (RAC) Opinion (05.12.13) for Lead (CAS# 7439-92-1): <http://echa.europa.eu/documents/10162/57ceb1ac-aafc-4852-9aa5-db81bcb04da3>

GHS Classification	Classification Procedure
Skin Sens. 1; H317	Threshold Calculation
Repr. 1A; H360DF	Threshold Calculation
Lact.; H362	Threshold Calculation

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
NTP	National Toxicology Program
IARC	International Agency for Research on Cancer
OSHA	The Occupational Safety & Health Administration
NIOSH	National Institute for Occupational Safety and Health

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.