

SAFETY DATA SHEET

Revision: 1.1 Date: 29.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name Gagekote 8
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.
- 1.2 Recommended use of the chemical and restrictions on use**
Identified Use(s) PC14 Metal surface treatment products, including galvanic and electroplating products.
Uses Advised Against None known.
- 1.3 Supplier's details**
Company Identification VISHAY MEASUREMENTS GROUP UK LTD
Stroudley Road
Basingstoke
Hampshire
RG24 8FW
United Kingdom
Telephone +44 (0) 1256 462131
Fax +44 (0) 1256 471441
E-Mail (competent person) mm.uk@vishaypg.com
- 1.4 Emergency Phone No.** (00-1) 703-527-3887
CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
- 2.1.1 Regulation (EC) No. 1272/2008 (CLP)** Flam. Liq. 2; H225
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336
Repr. 2; H361d
STOT RE 2; H373
- 2.1.2 Directive 67/548/EEC & Directive 1999/45/EC** F; R11: Highly flammable.
Xn; R65: Harmful: may cause lung damage if swallowed.
Xi; R36/38: Irritating to eyes and skin.
R67: Vapours may cause drowsiness and dizziness.
Repr. 3; R63: Possible risk of harm to the unborn child.
Xn; R48: Danger of serious damage to health by prolonged exposure.
- 2.2 Label elements**
Product Name According to Regulation (EC) No. 1272/2008 (CLP)
Gagekote 8
- Hazard Pictogram(s)
- 
- Signal Word(s) Danger
- Contains: Toluene and Methyl ethyl ketone

SAFETY DATA SHEET

Revision: 1.1 Date: 29.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

Hazard Statement(s)

H225: Highly flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H361d: Suspected of damaging the unborn child. - Inhalation
H373: May cause damage to organs through prolonged or repeated exposure:
Central nervous system - Inhalation.

Precautionary Statement(s)

P201: Obtain special instructions before use.
P210: Keep away from heat, hot surfaces, sparks, open flames and other
ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P337+P313: If eye irritation persists: Get medical advice/attention.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or
doctor/physician.
P331: Do NOT induce vomiting.

Additional Information

None.

2.3 Other hazards

None.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Toluene	45-55	108-88-3	203-625-9	None assigned	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Repr. 2; H361d STOT RE 2; H373
Methyl ethyl ketone	10-20	78-93-3	201-159-0	None assigned	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066

H225: Highly flammable liquid and vapour. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. H361d: Suspected of damaging the unborn child. H373: May cause damage to organs through prolonged or repeated exposure. EUH066: Repeated exposure may cause skin dryness or cracking.

Directive 67/548/EEC & Directive 1999/45/EC

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	EC Classification and Risk Phrases
Toluene	45 - 55	108-88-3	203-625-9	None assigned	F; R11 Xn; R65 Xi; R38 R67 Repr. 3; R63 Xn; R48
Methyl ethyl ketone	10-20	78-93-3	201-159-0	None assigned	F; R11 Xi; R36 R66

F; Flammable, Xi; Irritant, Xn; Harmful. R11: Highly flammable. R36: Irritating to eyes. R38: Irritating to skin. R48: Danger of serious damage to

SAFETY DATA SHEET

Revision: 1.1 Date: 29.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

health by prolonged exposure. R63: Possible risk of harm to the unborn child. R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. IF exposed or concerned: Get medical advice/attention.

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation occurs: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation develops or persists.

Ingestion

IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Drink two glasses of water. Do not give milk or alcoholic beverages. Do not give anything by mouth to an unconscious person. Immediately call a POISON CENTER/doctor.

4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. - Inhalation. May cause damage to organs through prolonged or repeated exposure: Central nervous system - Inhalation.

4.3 Indication of any immediate medical attention and special treatment needed

Do NOT induce vomiting, if vomiting does occur, have victim lean forward to reduce risk of aspiration. If Gastric Lavage is performed: Endotracheal control and/or esophagoscopy is recommended. Give a slurry of activated charcoal in water to drink. (240mL Water / 30 g Activated charcoal).

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media

As appropriate for surrounding fire. Extinguish preferably with foam, carbon dioxide or dry chemical.

Unsuitable extinguishing media

Do not use water jet. Direct water jet may spread the fire.

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. May decompose in a fire giving off toxic fumes. Oxides of carbon and Nitrogen oxides. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Avoid breathing vapours.

6.2 Environmental precautions

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Use non-sparking equipment when picking up flammable spill. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste

SAFETY DATA SHEET

Revision: 1.1 Date: 29.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

6.4 Reference to other sections (2008/98/EEC).
See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take precautionary measures against static discharge. Do not use sparking tools. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin, eyes or clothing. Do not breathe vapour. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
- 7.2 Conditions for safe storage, including any incompatibilities** Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight.
- Storage temperature Ambient. 5 - 25°C
Storage life Stable under normal conditions.
Incompatible materials Keep away from: Aerosol, Flammable liquid, Oxidizing agents, Corrosive Substances, Acids and Alkalis.
- 7.3 Specific end use(s)** PC14 Metal surface treatment products, including galvanic and electroplating products. See Section: 1.2.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Toulene	108-88-3	50	191	100	384	WEL
Methyl ethyl ketone	78-93-3	200	600	300	899	WEL

Note: WEL: Workplace Exposure Limit (UK HSE EH40)

- 8.1.2 Biological limit value** Not established.
- 8.1.3 PNECs and DNELs** Not established.
- 8.2 Exposure controls**
- 8.2.1 Appropriate engineering controls** Ensure adequate ventilation. or Use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems.
- 8.2.2 Individual protection measures, such as personal protective equipment (PPE)** General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Do not breathe vapour. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Body protection: Wear impervious protective clothing, including boots, lab coat,

SAFETY DATA SHEET

Revision: 1.1 Date: 29.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

Respiratory protection



Thermal hazards

8.2.3 Environmental Exposure Controls

apron or coveralls, as appropriate, to prevent skin contact.

In case of inadequate ventilation wear respiratory protection. Open system(s):
Wear suitable respiratory protective equipment.

Not applicable.

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Clear liquid with perceptible odour.
Odour	Aromatic.
Odour threshold	Not available.
pH	Not established.
Melting point/freezing point	Not established.
Initial boiling point and boiling range	82.2°C
Flash point	-1°C [Closed cup]
Evaporation rate	3.62 (BuAC = 1)
Flammability (solid, gas)	Not applicable - Liquid
Upper/lower flammability or explosive limits	Flammable Limits (Lower) (%v/v): 1.6 (Air) Flammable Limits (Upper) (%v/v): 11.2 (Air)
Vapour pressure	45.4 mmHg
Vapour density	4 (Air = 1)
Relative density	0.88 g/cm ³ (H ₂ O = 1)
Solubility(ies)	Water: 0.1%
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2 Other information

Volatile Organic Compound Content: 592 g/l

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Stability and reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Highly flammable liquid and vapour. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.
10.4 Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Do not use sparking tools.
10.5 Incompatible materials	Keep away from: Aerosol, Flammable liquid, Oxidizing agents, Corrosive Substances, Acids and Alkalis.
10.6 Hazardous decomposition product(s)	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide and Nitrogen oxides.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity

Ingestion

Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.

Inhalation

Based upon the available data, the classification criteria are not met.

SAFETY DATA SHEET

Revision: 1.1 Date: 29.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

Skin Contact	Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20.0 mg/l. Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
Skin corrosion/irritation	Skin Irrit. 2: Causes skin irritation.
Serious eye damage/irritation	Eye Irrit. 2: Causes serious eye irritation.
Respiratory or skin sensitization	Based upon the available data, the classification criteria are not met.
Germ cell mutagenicity	Based upon the available data, the classification criteria are not met.
Carcinogenicity	Based upon the available data, the classification criteria are not met.
Reproductive toxicity	Repr. 2: Suspected of damaging the unborn child. - Inhalation.
STOT - single exposure	STOT SE 3: May cause drowsiness or dizziness.
STOT - repeated exposure	STOT RE 2: May cause damage to organs through prolonged or repeated exposure: Central nervous system. - Inhalation.
Aspiration hazard	Asp. Tox. 1: May be fatal if swallowed and enters airways.
11.2 Other information	None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Based upon the available data, the classification criteria are not met. Estimated Mixture LC50 >100 mg/l (Fish)
12.2 Persistence and degradability	Part of the components are poorly biodegradable.
12.3 Bioaccumulative potential	The product has low potential for bioaccumulation.
12.4 Mobility in soil	The product is predicted to have low mobility in soil. (The product is essentially insoluble in water.)
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Other adverse effects	None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	This material and its container must be disposed of as hazardous waste (2008/98/EEC). Send after pre-treatment to a appropriate hazardous waste incinerator facility according to legislation.
13.2 Additional Information	Dispose of contents in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number	ADR/RID / IMDG / IATA UN 1263
14.2 Proper Shipping Name	PAINT
14.3 Transport hazard class(es)	3
14.4 Packing group	II
14.5 Environmental hazards	Not classified as a Marine Pollutant. / Environmentally hazardous substance
14.6 Special precautions for user	See Section: 2
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
14.8 Additional Information	None.

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1 EU regulations SVHCs	None
15.1.2 National regulations Germany	Water hazard class: 2
15.2 Chemical Safety Assessment	Not available.

SAFETY DATA SHEET

Revision: 1.1 Date: 29.04.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 453/2010

www.vishaypg.com

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Methyl ethyl ketone (CAS# 78-93-3) and Toluene (CAS# 108-88-3). Existing ECHA registration(s) for Methyl ethyl ketone (CAS# 78-93-3) and Toluene (CAS# 108-88-3).

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Flam. Liq. 2; H225	Flash Point [Closed cup] Test Result/ Boiling Point (°C)
Asp. Tox. 1; H304	Estimated Viscosity
Skin Irrit. 2; H315	Threshold Calculation
Eye Irrit. 2; H319	Threshold Calculation
STOT SE 3; H336	Threshold Calculation
Repr. 2; H361d	Threshold Calculation
STOT RE 2; H373	Threshold Calculation

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.