

Wide Range Strain Indicator



A versatile high-performance laboratory-type instrument featuring wide-range operating controls for handling the most critical strain measuring tasks.

FEATURES

- 4-1/2 Digit LED Display
- ANSI/SEM Color-coded bridge connection terminals
- Analog output
- Transducer connector with remote sense
- Direct reading of strain, pressure, torque, load, and other engineering variables
- Convenient color-coded push-button controls
- Gage factor range from 0.0500 to 50.00 displayed on LED readout (to four significant digits)
- Bridge excitation range from 1.000 to 15.000Vdc
- Extremely wide balance range. Balance by voltage injection
- Quarter-, half-, and full-bridge circuits
- Built-in 120/1000 Ω and 350 Ω bridge completion
- Separate bridge excitation on/off control

DESCRIPTION

EXCEPTIONAL RANGE • RESOLUTION • VERSATILITY NEVER BEFORE ACHIEVED IN A LABORATORY INSTRUMENT

The Model 3800 Wide Range Strain Indicator is a versatile, high-precision laboratory-type instrument designed for use with strain gages and strain gage based transducers.

Principal features of the Model 3800 are wide-range control of gage factor; excitation precisely settable over 1 - 15 volt range; and wide balance range with no bridge loading effect.

With these extended operating capabilities, the Model 3800 can be used for the most demanding measurement tasks which are not possible with conventional strain measuring instruments and general-purpose transducer indicators. Resolutions achievable with the Model 3800 are 0.10 $\mu\epsilon$ when used as a strain indicator, and 0.10 $\mu\text{V/V}$ when used as a transducer indicator (0.025 $\mu\text{V/V}$ with suppressed zero).

In addition to the wide-range features, the Model 3800 incorporates simplified operating controls that minimize set-up time, and promote measurement accuracy. The operator follows a logical sequence of steps to configure the instrument for the desired measurement. Color-coded interlocked push-button controls minimize operator errors, and make the operating mode instantly recognizable.

Gage factor on the Model 3800 is settable by front-panel controls over a range of 0.0500 to 50.00, and is displayed by the LED readout when in the SET position. The instrument allows full range display ($\pm 19\,999$ counts) over the complete gage factor range.

Excitation voltage is precisely settable over a range of 1 - 15 volts in 1-volt increments by a front-panel thumbwheel switch. The output display automatically tracks the excitation setting so that gage factor does not vary with bridge voltage.

The balance system in the Model 3800 has four ranges which are selected by the BALANCE RANGE push buttons. Each range is further divided into four sub ranges by the COARSE balance switch. The FINE balance control provides an additional adjustment range that overlaps the COARSE balance switch positions. This unique system provides a total of 32 overlapping ranges for achieving precise balance settings and resolution. All balance voltages are electronically injected into the input amplifier to eliminate bridge loading errors and preserve full measurement range.

The instrument will accept full-, half-, or quarter-bridge strain gage inputs; and all required bridge completion components for 120, 350, and 1000 Ω gages are built in. Shunt-calibration resistors across the internal dummies are provided on the rear panel. Two remote calibration resistors, also mounted on the rear panel, are actuated by the front-panel calibration button.

Virtually all strain gage based transducers can be used with the Model 3800 via the rear-panel transducer connector. This connector provides precision remote sense capability, as well as access to the remote calibration resistors. Full-scale resolutions of 0.10 $\mu\text{V/V}$ are routinely possible. By using the wide-range balance controls to suppress zero, resolutions to 0.025 $\mu\text{V/V}$ can be achieved.

In addition to the digital LED display, the Model 3800 provides an analog output available at the rear panel. A separate analog level control totally independent of the digital display is also provided.

The Model 3800 Wide Range Strain Indicator is an exceptional, high-resolution instrument that will make a valuable contribution to any experimental stress analysis or transducer development laboratory.

Wide Range Strain Indicator

SPECIFICATIONS

Range and Display:

±19 999 counts direct-reading LED display.

Resolution:

1 $\mu\epsilon$ at any gage factor from 0.0500 to 50.00.
 0.10 $\mu\text{V/V}$ as a transducer indicator.

Linearity:

±0.01% of full scale.

Balance Range:

Coarse balance: ±2.5% to ±100% of full scale per step, in 32 total steps.

Fine balance: ±1.25% to ±50% of full scale; overlaps each coarse balance step.

Balance Method:

Electronically injected counter-emf.

Gage Factor:

Range: 0.0500 to 50.00; displayed by LED readout when in the SET position.

Resolution:

0.0001 from GF of 0.0500 to 0.5000

0.001 from GF of 0.500 to 5.000

0.01 from GF of 5.00 to 50.00

Linearity: ±0.05% of full scale.

Accuracy: ±1 least significant digit.

Excitation Voltage:

1.000 to 15.000Vdc±1mV±0.02%. Settable in 1V increments by front-panel thumbwheel switch.

Temperature stability: ±0.01%/°C.

Amplifier:

Temperature effect on zero: ±1.0 $\mu\text{V}/^\circ\text{C}$ RTI[†] max.;
 ±0.50 $\mu\text{V}/^\circ\text{C}$ RTI[†] typical.

Temperature effect on span: ±0.005%/°C max.

Warm-up drift: less than ±3 μV RTI[†] from turn-on to 5 minutes.

Random drift at constant ambient temperature: less than ±1 μV RTI[†].

Common-mode rejection: greater than 100dB at 50-60Hz.

Common-mode voltage: ±8V max.

Input impedance: greater than 100M Ω differential and common mode.

Input circuits: quarter-, half-, and full-bridge circuits. Internal bridge completion provided for 120/1000 Ω and 350 Ω quarter bridges; 60 to 2000 Ω half or full bridge.

Calibration: shunt calibration resistors are provided across internal 120 Ω and 350 Ω dummy gages to simulate 5000 $\mu\epsilon$ ±0.05%. Calibration resistors are located on the rear of instrument and may be changed to suit specific requirements. Contact closures are provided for two rear-panel-mounted resistors to facilitate any calibration configuration. Typical use is double-shunt calibration of transducers.

Analog Output:

Linear output: ±10.00V max; adjustable over 11:1 range by a ten-turn potentiometer mounted on the rear panel.

Output load: 2k Ω min.

Bandwidth: GF >0.500, dc to 4.5kHz (−3 dB nominal).
 GF <0.500, dc to 2.0kHz (−3 dB nominal).

Output noise: less than 2.5 μV peak to peak 0.10 to 10Hz, RTI[†]. Less than 2 μV rms dc to 5kHz, RTI[†], plus 0.005% of full scale, RTO (referred to output).

Remote Sense:

Remote sense connections provided at transducer connector.

Remote sense error: less than 0.0005%/ Ω of lead resistance. Maximum lead resistance 40 Ω or less.

Power:

115/230Vac, 50-60Hz, less than 10 volt-amperes.

Size and Weight:

6.5 H x 11.0 W x 12.5 D in (165 x 280 x 318mm).

10.2lb (4.6kg).

[†]Referred to input

All specifications are nominal or typical at +23°C unless noted.

Companion instruments for use with the Model 3800

Model V/E-40 Decade Resistor Strain Gage Simulator, and Model 1550A Strain Indicator Calibrator — with these specialized instruments, the capabilities and sensitivity of the Model 3800 can be further extended by making critical measurements through precise strain simulation.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.