

NOTES:

- 1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5-1982.
- 2. DATUM PLANE —H— IS LOCATED AT MOLD PARTING LINE AND COINCIDENT WITH LEAD, WHERE LEAD EXITS PLASTIC BODY AT BOTTOM OF PARTING LINE.
- 3. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.25 MM ON D1 AND E1 DIMENSIONS.
- 4. THE TOP OF PACKAGE IS SMALLER THAN THE BOTTOM OF PACKAGE BY 0.15 MILLIMETERS.
- 5. DIMENSION 6 DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 MM TOTAL IN EXCESS OF THE 6 DIMENSION AT MAXIMUM MATERIAL CONDITION.
- 6. ALL DIMENSIONS ARE IN MILLIMETERS.
- 7. THIS DUTLINE CONFORMS TO JEDEC PUBLICATION 95, REGISTRATION MS-026.
- 8. LEADS SHALL BE COPLANAR WITHIN .004 INCH.
- 9. EXPOSED DIE PAD SHALL BE COPLANAR WITH BOTTOM OF PACKAGE $_{\Lambda}$ WITHIN 2 MILS (.05 MM).
- 10) DIMENSIONS X AND Y APPLY TO EXPOSED PAD (EP) VERSIONS ONLY. SEE INDIVIDUAL PRODUCT DATASHEET TO DETERMINE IF A PRODUCT USES EXPOSED PAD PACKAGE.
- /11 MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- 12. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PEFREE (+) PKG. CODES.

	COMMON DIMENSIONS				
	DIMENSIONS IN MILLIMETERS				
	JEDEC AAA-HD				
	5×5×1.0 MM				
	MIN.	MAX.			
Α	*	1.20			
A ₁	0.05	0,15			
Aa	0.95	1.05			
D	6.80	7,20			
D ₁	4.80	5.20			
Е	6.80	7.20			
E ₁	4.80	5.20			
L	0.45	0.75			
N	32				
е	0.50 BSC.				
b	0.17	0.27			
b1	0.17	0.23			
C	0.09	0.20			
⊂1	0.09	0.16			

		X (mm)		Y (mm)	
PKG (CODE	MIN.	MAX.	MIN.	MAX.
H32E-5		2.8	3,2	2,8	3,2
H32E-6		3,2	3.6	3,2	3,6



TITLE:

PACKAGE DUTLINE, 32L TQFP, 5x5x1.0mm, EP DPTIDN

APPROVAL DOCUMENT CONTROL NO.

REV.

21-0079