

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
- 2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- 3. "N" IS THE TOTAL NUMBER OF TERMINALS.
- THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED.THE TERMINAL #1 DENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- DIMENSION 6 APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25 mm AND 0.30 mm FROM TERMINAL TIP.
- 6. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH "D" AND "E" SIDE RESPECTIVELY.
- 7. DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
- $ilde{m{\&}}$ COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
- 9. WARPAGE SHALL NOT EXCEED 0.10 mm.
- 10. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
- 11. ALL DIMENSIONS APPLY BOTH TO LEAD FREE (+) & LEADED (-) PKG. CODES.
- 12. PACKAGE CODE: L4877F-15 L4877F-6

SYMBOLS	COMMON DIMENSIONS		
	MIN.	N□M.	MAX.
Α	1,20	1.30	1.40
A1	-	0.58	_
D	6.90	7.00	7.10
D2	4.70	4.90	5.10
E	6,90	7.00	7.10
E2	4.70	4.90	5.10
L	0.42	0.47	0.52
L1	_	_	0.10
b	0.20	0.25	0.30
e	1	0.50	ı
Z	48		
ND	12		
NE	12		



TITLE: PACKAGE OUTLINE, 48L LGA 7x7x1.4mm,

APPROVAL

DOCUMENT CONTROL NO. 21-0152

REV.

