

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
- 2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- "N" IS THE TOTAL NUMBER OF TERMINALS.
- /4、 THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED.THE TERMINAL #1 DENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- √S DIMENSION 6 APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25 mm AND 0.30 mm FROM TERMINAL TIP.
- 6. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH "D" AND "E" SIDE, RESPECTIVELY.
- DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
- /8). COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
- WARPAGE SHALL NOT EXCEED 0.10 mm.
- 10. MARKING IS FOR PACKAGE ORIENTATION ONLY.
- 11. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
- 12. ALL DIMENSIONS APPLY BOTH TO LEAD FREE (+) & LEADED (-) PKG. CODES.
- 13. PACKAGE CODE: L4877T-1

°>™BO¬	COMMON DIMENSIONS			N _O T _E
0 L	MIN.	N□M.	MAX.	
Α	0.70	0.75	0.80	
A1	ı	1	0,25	
D	6.90	7.00	7.10	
D2	2.80	99 2. 90	3.00	
Ε	6,90	7.00	7.10	
E2	2.80	2.90	3,00	
L	0,35	0.45	0,55	
L1	0.30	0.38	0.45	
b	0.20	0.25	0.30	
е	0.50 BSC			
Ν	48			
ND	12			
NE	12			



7x7x0.8mm DOCUMENT CONTROL NO.

APPROVAL

21-0166

В

