

REF.	MIN.	N□M.	MAX.	NOTE
Α	0.70	0.75	0.80	
A1	0	ı	0.05	
A3	0			
b	0.20	0.25	0.30	
D	4.90	5.00	5.10	
E	5.90	6.00	6.10	
е	0			
k	0.25	ı	1	
L	0.35	0.40	0.45	ALL PINS
N				
ND				
NE				

EXPOSED PAD VARIATIONS								
PKG.	D2			E2				
CODE	MIN.	N□M.	MAX.	MIN.	N□M.	MAX.		
T3256-1	3.50	3.60	3.70	4.50	4.60	4.70		
T3256MN-1	3.50	3.60	3.70	4.50	4.60	4.70		

NOTES:

- DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- 2. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
- 3. N IS THE TOTAL NUMBER OF TERMINALS.
- THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012.

 DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- DIMENSION 6 APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25mm AND 0.30mm FROM TERMINAL TIP.
- 6. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE RESPECTIVELY.
- / DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
- /8/ COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
- 9. REFER TO JEDEC MO-220 (WHJD) EXCEPT D2 & E2 DIMENSIONS.
- 10. WARPAGE SHALL NOT EXCEED 0.10mm.
- <u>√1</u>
 MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- 12. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND POFREE (+) PKG. CODES.



TITLE:

PACKAGE DUTLINE, 32L THIN QFN, 5x6x0.75mm

APPROVAL

DOCUMENT CONTROL NO.