

| COMM | N D | | | |
|------|--------|----------|------|-------------|
| REF. | MIN. | N□M. | MAX. | T E |
| Α | 0.70 | 0.75 | 0.80 | |
| A1 | 0 | ı | 0.05 | |
| A3 | | | | |
| b | 0.15 | 0.20 | 0,25 | \triangle |
| D | 3.40 | 3.50 | 3.60 | |
| E | 3.40 | 3.50 | 3.60 | |
| е | 1 | | | |
| K | 0.25 | _ | 1 | |
| L | 0.30 | 0.35 | 0.40 | |
| N | | | | |
| ND | | 6 | | |
| NE | 6 | | | <u>(6)</u> |

| EXPOSED PAD VARIATIONS | | | | | | |
|------------------------|------|------|------|------|------|------|
| | | D2 | | | E2 | |
| | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. |
| T243A3-1 | 2.20 | 2.30 | 2.40 | 2.20 | 2.30 | 2.40 |
| T243A3-1C | 2.20 | 2.30 | 2.40 | 2.20 | 2.30 | 2.40 |

| CORNER LEAD CHAMFER VARIATION | | | | |
|----------------------------------|----------------|----------|--|--|
| PKG. CODES | С | L4 | | |
| T243A3-1 | 0.03 X 45° REF | 0.33 REF | | |
| T243A3-1C | 0.03 X 45° REF | 0.33 REF | | |

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS, ANGLES IN DEGREES UNLESS OTHERWISE SPECIFIED
- 2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- 3. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
- THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- DIMENSION 6 APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25mm AND 0.30mm FROM TERMINAL TIP.
- $\angle 6$. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE RESPECTIVELY.
 7. DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
 - COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
- $\sqrt{9}$. APPLICABLE ONLY FOR PACKAGES WITH TIGHT CORNER LEADS METAL TO METAL CLEARANCE.
- 10. REFER TO JEDEC MO-220 EXCEPT D2, E2, & L DIMENSIONS.
- 1,1. WARPAGE SHALL NOT EXCEED 0.10mm.
- $\cancel{12}$ marking shown is for package orientation purpose only.
- 13. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PHFREE (+) PKG. CODES.



TITLE:

PACKAGE DUTLINE,

24L THIN QFN 3.5×3.5×0.75MM

APPROVAL DOCUMENT CONTROL NO. 21-0188

REV.