





|TITLE:

PACKAGE DUTLINE, 16L SAWN QFN, 5X5X0.90MM

APPROVAL RAMON DE LEON 12/21/11 DOCUMENT CONTROL NO. 21-0643

REV. 1/2

NULTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS, ANGLES ARE IN DEGREES.
- 2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- 3. N IS THE TOTAL NUMBER OF TERMINALS.
- THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- 5. DIE THICKNESS ALLOWABLE IS 0.305 mm MAXIMUM(.012 INCHES MAXIMUM)
- 6. PACKAGE WARPAGE MAX 0.08 mm.
- DIMENSION & APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.15 mm AND 0.30 mm FROM TERMINAL TIP.
- APPLIED FOR EXPOSED PAD AND TERMINALS, EXCLUDE EMBEDDING PART OF EXPOSED PAD FROM MEASURING.
- 9. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE, RESPECTIVELY.
- /1Ò, COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
 11. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10−0131.
- 12 MARKING SHOWN IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- 13. NI/PD/AU LEAD FINISH.
- 14. ALL DIMENSIONS APPLY TO POFREE (+) PKG. CODES.
- 15. PACKAGE CODE: G1655N-1

SYMBOL	MILLIMETER			INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
Α			0.90			.035
A1		-	0.05			.002
A2		0.65	0.70		.026	.028
А3	0.20 REF.			.008 REF.		
b	0.35	0.40	0.45	.014	.016	.018
D	4.9	5.0	5.1	.193	.197	.201
D2	3.10	3.20	3.30	.122	.126	.130
Е	4.9	5.0	5.1	.193	.197	.201
E2	3.10	3.20	3.30	.122	.126	.130
k	MIN 0.2			800. NIM		
L	0.35	0.55	0.75	.014	.022	.030
е	0.80 BSC			.031 BSC		
R	0.175			.007		
TOLERANCES OF FORM AND POSITION						
aaa	0.10			.004		
bbb	0.10			.004		
ccc	0.05			.002		



TITLE

PACKAGE DUTLINE, 16L SAWN QFN, 5X5X0.90MM

APPROVAL RAMON DE LEON 12/21/11 DOCUMENT CONTROL NO. 21-0643