

TDA3663

Very low dropout voltage/quiescent current 3.3 V voltage regulator

Rev. 06 — 26 June 2007

Product data sheet

1. General description

The TDA3663 is a fixed 3.3 V voltage regulator with a very low dropout voltage and quiescent current, which operates over a wide supply voltage range.

2. Features

- Fixed 3.3 V, 100 mA regulator
- Supply voltage range up to 45 V
- Very low quiescent current of 15 μ A (typical value)
- Very low dropout voltage
- High ripple rejection
- Protections:
 - ◆ Reverse polarity safe (down to -25 V without high reverse current)
 - ◆ Negative transient of 50 V ($R_S = 10 \Omega$, $t < 100$ ms)
 - ◆ Able to withstand voltages up to 18 V at the output (supply line may be short-circuited)
 - ◆ ESD protection on all pins
 - ◆ DC short-circuit safe to ground and V_P of the regulator output
 - ◆ Temperature protection (at $T_j > 150$ °C)

3. Quick reference data

Table 1: Quick reference data

$V_P = 14.4\text{ V}$; $T_{amb} = 25\text{ }^\circ\text{C}$; measured with test circuit of [Figure 15](#); unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|--|-------------------|---|-------|------|------|------|
| Supply voltage: pin V_P | | | | | | |
| V _P | supply voltage | regulator operating | [1] 3 | 14.4 | 45 | V |
| I _q | quiescent current | V _P = 4.5 V; I _{REG} = 0 mA | - | 10 | - | μA |
| | | V _P = 14.4 V; I _{REG} = 0 mA | - | 15 | 30 | μA |
| | | 6 V ≤ V _P ≤ 22 V; I _{REG} = 10 mA | - | 0.2 | 0.5 | mA |
| | | 6 V ≤ V _P ≤ 22 V; I _{REG} = 50 mA | - | 1.4 | 2.5 | mA |
| Regulator output: pin REG | | | | | | |
| V _{REG} | output voltage | 8 V ≤ V _P ≤ 22 V; I _{REG} = 0.5 mA | 3.16 | 3.3 | 3.44 | V |
| | | 0.5 mA ≤ I _{REG} ≤ 100 mA | 3.13 | 3.3 | 3.47 | V |
| | | 6 V ≤ V _P ≤ 45 V; I _{REG} = 0.5 mA; | 3.13 | 3.3 | 3.47 | V |
| V _{REG(drop)} | dropout voltage | V _P = 3.1 V; T _{amb} ≤ 85 °C; I _{REG} = 50 mA; | - | 0.18 | 0.3 | V |


[1] The regulator output will follow V_P if V_P < V_{REG} + V_{REG(drop)}.

4. Ordering information

Table 2: Ordering information

| Type number | Package | | Version |
|-------------|---------|---|----------|
| | Name | Description | |
| TDA3663 | SO4 | plastic small outline package; 4 leads; body width 3.5 mm | SOT223-1 |
| TDA3663AT | SO8 | plastic small outline package; 8 leads; body width 3.9 mm | SOT96-1 |

5. Block diagram



6. Pinning information

6.1 Pinning




Fig 2. Pin configuration for SO4

Fig 3. Pin configuration for SO8

6.2 Pin description

Table 3: Pin description

| Symbol | Pin | | Description |
|----------------|---------|---------------|-----------------------|
| | SO4 | SO8 | |
| V _P | 1 | 8 | supply voltage |
| GND | 2 and 4 | 2, 3, 6 and 8 | ground ^[1] |
| REG | 3 | 1 | regulator output |
| n.c. | - | 4 and 5 | not connected |

[1] For the SO8 package all GND pins are connected to the lead frame and can also be used to reduce the total thermal resistance $R_{th(j-a)}$ by soldering these pins to a ground plane. The ground plane on the top side of the PCB acts like a heat spreader.

7. Functional description

The TDA3663 is a fixed 3.3 V regulator which can deliver output currents up to 100 mA. The regulator is available in SO8 and SO4 packages. The regulator is intended for portable, mains and telephone applications. To increase the lifetime of batteries, a specially built-in clamp circuit keeps the quiescent current of this regulator very low, also in dropout and full load conditions.

The device remains operational down to very low supply voltages and below this voltage it switches off.

A temperature protection circuit is included which switches off the regulator output at a junction temperature above 150 °C.

8. Limiting values

Table 4: Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|--------------------|---------------------------------|-------------------------------------|-----|------|------|
| V _P | supply voltage | | - | 45 | V |
| V _{P(rp)} | reverse polarity supply voltage | non-operating | - | -25 | V |
| P _{tot} | total power dissipation | | | | |
| | TDA3663 | temperature of copper area is 25 °C | - | 4.1 | W |
| | TDA3663AT | T _{amb} = 25 °C | - | 5 | W |
| T _{stg} | storage temperature | non-operating | -55 | +150 | °C |
| T _{amb} | ambient temperature | operating | -40 | +125 | °C |
| T _j | junction temperature | operating | -40 | +150 | °C |

9. Thermal characteristics

Table 5: Thermal characteristics

| Symbol | Parameter | Conditions | Typ | Unit |
|---------------|---|--------------------------|-----|------|
| $R_{th(j-a)}$ | thermal resistance from junction to ambient | | | |
| | SO4 | in free air; soldered | 100 | K/W |
| | SO8 | in free air; soldered | 155 | K/W |
| $R_{th(j-c)}$ | thermal resistance from junction to case | | | |
| | SO4 | to center pins; soldered | 25 | K/W |
| | SO8 | to center pins; soldered | 30 | K/W |

10. Characteristics

Table 6: Characteristics

$V_P = 14.4$ V; $T_{amb} = 25$ °C; measured with test circuit of [Figure 15](#); unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---|--|---|-------|------|------|------|
| Supply voltage: pin V_P | | | | | | |
| V_P | supply voltage | regulator operating | [1] 3 | 14.4 | 45 | V |
| I_q | quiescent current | $V_P = 4.5$ V; $I_{REG} = 0$ mA | - | 10 | - | μA |
| | | $V_P = 14.4$ V; $I_{REG} = 0$ mA | - | 15 | 30 | μA |
| | | 6 V $\leq V_P \leq 22$ V; $I_{REG} = 10$ mA | - | 0.2 | 0.5 | mA |
| | | 6 V $\leq V_P \leq 22$ V; $I_{REG} = 50$ mA | - | 1.4 | 2.5 | mA |
| Regulator output: pin REG | | | | | | |
| V_{REG} | output voltage | 8 V $\leq V_P \leq 22$ V; $I_{REG} = 0.5$ mA | 3.16 | 3.3 | 3.44 | V |
| | | 0.5 mA $\leq I_{REG} \leq 100$ mA | 3.13 | 3.3 | 3.47 | V |
| | | 6 V $\leq V_P \leq 45$ V; $I_{REG} = 0.5$ mA | 3.13 | 3.3 | 3.47 | V |
| $V_{REG(drop)}$ | dropout voltage | $V_P = 3.1$ V; $T_{amb} \leq 85$ °C; $I_{REG} = 50$ mA | - | 0.18 | 0.3 | V |
| $V_{REG(stab)}$ | output voltage long-term stability | per 1000 h | - | 20 | - | mV |
| $\Delta V_{REG(line)}$ | line input regulation voltage | 7 V $\leq V_P \leq 22$ V; $I_{REG} = 0.5$ mA | - | 1 | 30 | mV |
| | | 7 V $\leq V_P \leq 45$ V; $I_{REG} = 0.5$ mA | - | 1 | 50 | mV |
| $\Delta V_{REG(load)}$ | load output regulation voltage | 0.5 mA $\leq I_{REG} \leq 50$ mA | - | 10 | 50 | mV |
| SVRR | supply voltage ripple rejection | $f_i = 120$ Hz; $V_{i(ripple)} = 1$ V (RMS); $I_{REG} = 0.5$ mA | 50 | 60 | - | dB |
| $I_{REG(crl)}$ | output current limit | $V_{REG} > 2.8$ V | 0.17 | 0.25 | - | A |
| $I_{LO(rp)}$ | output leakage current at reverse polarity | $V_P = -15$ V; $V_{REG} \leq 0.3$ V | - | 1 | 500 | μA |

[1] The regulator output will follow V_P if $V_P < V_{REG} + V_{REG(drop)}$.

11. Application information

11.1 Noise

The output noise is determined by the value of the output capacitor. The noise figure is measured at a bandwidth of 10 Hz to 100 kHz (see [Table 7](#)).

Table 7: Noise figures

| Output current I_{REG} (mA) | Noise figure (μ V) | | |
|-------------------------------|-------------------------|-----------------|------------------|
| | C2 = 10 μ F | C2 = 47 μ F | C2 = 100 μ F |
| 0.5 | 550 | 320 | 300 |
| 50 | 650 | 400 | 400 |

11.2 Stability

For stable operation:

- The maximum output capacitor ESR should not exceed 22 Ω (worst-case) and for the minimum ESR, see [Table 8](#).
- The ESR of the output capacitor is limited.
- See [Table 8](#) for the minimum ESR values of the output capacitor, at T_{amb} given the load and output capacitance.

Remark: In the event of using different types of capacitors, a minimum ESR needs to be created by using an additional resistor that is placed in series with the output capacitor, see [Figure 4](#).

- It is recommended not to use below 1 mA output current because of reduced phase margin.

Table 8: Minimum ESR values required

| I_{REG} (mA) max | C2 = 100 nF | C2 = 1 μ F | C2 = 10 μ F | C2 = 100 μ F |
|--------------------|--------------|----------------|-----------------|------------------|
| 1 | > 0 Ω | > 1.5 Ω | > 2.5 Ω | > 0 Ω |
| 5 | > 1 Ω | > 0.5 Ω | > 1 Ω | > 0 Ω |
| 10 | > 0 Ω | > 0.5 Ω | > 4 Ω | > 0 Ω |
| 100 | > 0 Ω | > 0.5 Ω | > 4 Ω | > 0 Ω |

11.3 Application circuits

The maximum output current of the regulator equals:

$$I_{REG(max)} = \frac{150 - T_{amb}}{R_{th(j-a)} \times (V_P - V_{REG})} = \frac{150 - T_{amb}}{100 \times (V_P - 3.3)} (mA)$$

When $T_{amb} = 21$ °C and $V_P = 14$ V the maximum output current equals 116 mA.


The total thermal resistance of the TDA3663 can be decreased from 155 K/W to 30 K/W for the SO8 version. For the SO4 version it can be decreased from 100 K/W to 25 K/W when GND pins 2 and 4 of the package are soldered to the printed-circuit board.

11.3.1 Application circuit with backup function

Sometimes a backup function is needed to supply, for example, a microcontroller for a short period of time when the supply voltage spikes to 0 V (or even -1 V).


This function can easily be built with the TDA3663 by using an output capacitor with a large value. When the supply voltage is 0 V (or -1 V), only a small current will flow into pin REG from this output capacitor (a few μA).

The application circuit is given in [Figure 4](#).



11.4 Additional application information

This section gives typical curves for various parameters measured on the TDA3663AT. Standard test conditions are: $V_P = 14.4\text{ V}$; $T_{amb} = 25\text{ }^\circ\text{C}$.



$I_{REG} = 0\text{ mA}$.

Fig 5. Quiescent current as a function of the supply voltage






Fig 6. Quiescent current increase as a function of the high supply voltage




$I_{REG} = 10\text{ mA}$.

Fig 7. Quiescent current as a function of the supply voltage



$I_{REG} = 50\text{ mA}$.

Fig 8. Quiescent current as a function of the supply voltage



- (1) I_q at 50 mA load.
- (2) I_q at 10 mA load.

Fig 9. Quiescent current as a function of the junction temperature





Fig 10. Quiescent current as a function of the output current



$I_{REG} = 0$ mA.

Fig 11. Output voltage thermal protection as a function of the junction temperature







Fig 12. Dropout voltage as a function of the output current



12. Test information



12.1 Quality information

The *General Quality Specification for Integrated Circuits, SNW-FQ-611* is applicable.

13. Package outline

SO4: plastic small outline package; 4 leads; body width 3.5 mm

SOT223-1




Fig 16. Package outline SOT223-1 (SO4)

SO8: plastic small outline package; 8 leads; body width 3.9 mm

SOT96-1




Fig 17. Package outline SOT96-1 (SO8)

14. Revision history

Table 9: Revision history

| Document ID | Release date | Data sheet status | Change notice | Doc. number | Supersedes |
|---------------|---|---------------------------|---------------|----------------|------------|
| TDA3663_6 | 20070626 | Product data sheet | - | - | TDA3663_5 |
| Modifications | <ul style="list-style-type: none"> • The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors. • Legal texts have been adapted to the new company name where appropriate. • Minor changes made to bulleted list in Section 11.2 • Minor changes made to Table 8 • Component additions to Figure 4 and Figure 15. | | | | |
| TDA3663_5 | 20050613 | Product data sheet | - | 9397 750 15047 | TDA3663_4 |
| TDA3663_4 | 20001214 | Product specification | - | 9397 750 07864 | TDA3663_3 |
| TDA3663_3 | 20001208 | Preliminary specification | - | 9397 750 07555 | TDA3663_2 |
| TDA3663_2 | 20000201 | Preliminary specification | - | 9397 750 06798 | TDA3663_1 |
| TDA3663_1 | 19990929 | Preliminary specification | - | 9397 750 06068 | - |

15. Legal information

15.1 Data sheet status

| Document status ^{[1][2]} | Product status ^[3] | Definition |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

15.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

15.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or

malfunction of a NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

16. Contact information

For additional information, please visit: <http://www.nxp.com>

For sales office addresses, send an email to: salesaddresses@nxp.com

17. Contents

| | | |
|-----------|--|-----------|
| 1 | General description | 1 |
| 2 | Features | 1 |
| 3 | Quick reference data | 2 |
| 4 | Ordering information | 2 |
| 5 | Block diagram | 2 |
| 6 | Pinning information | 3 |
| 6.1 | Pinning | 3 |
| 6.2 | Pin description | 4 |
| 7 | Functional description | 4 |
| 8 | Limiting values | 4 |
| 9 | Thermal characteristics | 5 |
| 10 | Characteristics | 5 |
| 11 | Application information | 6 |
| 11.1 | Noise | 6 |
| 11.2 | Stability | 6 |
| 11.3 | Application circuits | 6 |
| 11.3.1 | Application circuit with backup function | 7 |
| 11.4 | Additional application information | 8 |
| 12 | Test information | 10 |
| 12.1 | Quality information | 10 |
| 13 | Package outline | 11 |
| 14 | Revision history | 13 |
| 15 | Legal information | 14 |
| 15.1 | Data sheet status | 14 |
| 15.2 | Definitions | 14 |
| 15.3 | Disclaimers | 14 |
| 15.4 | Trademarks | 14 |
| 16 | Contact information | 14 |
| 17 | Contents | 15 |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.



© NXP B.V. 2007.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 26 June 2007

Document identifier: TDA3663_6