

# CD4007UB Types

## CMOS Dual Complementary Pair Plus Inverter

High-Voltage Types (20-Volt Rating)

■ CD4007UB types are comprised of three n-channel and three p-channel enhancement-type MOS transistors. The transistor elements are accessible through the package terminals to provide a convenient means for constructing the various typical circuits as shown in Fig. 2.


More complex functions are possible using multiple packages. Numbers shown in parentheses indicate terminals that are connected together to form the various configurations listed.

The CD4007UB types are supplied in 14-lead hermetic dual-in-line ceramic packages (F3A suffix), 14-lead dual-in-line plastic packages (E suffix), 14-lead small-outline packages (M, MT, M96, and NSR suffixes), and 14-lead thin shrink small-outline packages (PW and PWR suffixes).

### Applications:


- Extremely high-input impedance amplifiers
- Shapers
- Inverters
- Threshold detector
- Linear amplifiers
- Crystal oscillators

### TERMINAL DIAGRAM Top View



### Features:

- Standardized symmetrical output characteristics
- Medium Speed Operation –  $t_{PHL}$ ,  $t_{PLH}$  = 30 ns (typ.) at 10 V
- 100% tested for quiescent current at 20 V
- Meets all requirements of JEDEC Tentative Standard No. 13B, "Standard Specifications for Description of 'B' Series CMOS Devices"
- Maximum input current of 1  $\mu$ A at 18 V over full package-temperature range; 100 nA at 18 V and 25°C



### RECOMMENDED OPERATING CONDITIONS

For maximum reliability, nominal operating conditions should be selected so that operation is always within the following ranges:

| CHARACTERISTIC   | LIMITS |      | UNITS |
|--|--------|------|-------|
|  | MIN.   | MAX. |       |
| Supply-Voltage Range<br>(For $T_A$ = Full Package Temperature Range) | 3      | 18   | V     |

### STATIC ELECTRICAL CHARACTERISTICS

| CHARACTERISTIC                              | CONDITIONS   |                 |                 | LIMITS AT INDICATED TEMPERATURES (°C) |           |         |         |       |               |           | UNITS   |
|---|--------------|-----------------|-----------------|---------------------------------------|-----------|---------|---------|-------|---------------|-----------|---------|
|   | $V_O$<br>(V) | $V_{IN}$<br>(V) | $V_{DD}$<br>(V) | +25                                   |           |         |         |       |               |           |         |
|   |              |                 |                 | -55                                   | -40       | +85     | +125    | Min.  | Typ.          | Max.      |         |
| Quiescent Device Current, $I_{DD}$ Max.     | –            | 0,5             | 5               | 0,25                                  | 0,25      | 7,5     | 7,5     | –     | 0,01          | 0,25      | $\mu$ A |
|   | –            | 0,10            | 10              | 0,5                                   | 0,5       | 15      | 15      | –     | 0,01          | 0,5       |         |
|   | –            | 0,15            | 15              | 1                                     | 1         | 30      | 30      | –     | 0,01          | 1         |         |
|   | –            | 0,20            | 20              | 5                                     | 5         | 150     | 150     | –     | 0,02          | 5         |         |
| Output Low (Sink) Current, $I_{OL}$ Min.    | 0,4          | 0,5             | 5               | 0,64                                  | 0,61      | 0,42    | 0,36    | 0,51  | 1             | –         | mA      |
|   | 0,5          | 0,10            | 10              | 1,6                                   | 1,5       | 1,1     | 0,9     | 1,3   | 2,6           | –         |         |
|   | 1,5          | 0,15            | 15              | 4,2                                   | 4         | 2,8     | 2,4     | 3,4   | 6,8           | –         |         |
| Output High (Source) Current, $I_{OH}$ Min. | 4,6          | 0,5             | 5               | -0,64                                 | -0,61     | -0,42   | -0,36   | -0,51 | -1            | –         | mA      |
|   | 2,5          | 0,5             | 5               | -2                                    | -1,8      | -1,3    | -1,15   | -1,6  | -3,2          | –         |         |
|   | 9,5          | 0,10            | 10              | -1,6                                  | -1,5      | -1,1    | -0,9    | -1,3  | -2,6          | –         |         |
|   | 13,5         | 0,15            | 15              | -4,2                                  | -4        | -2,8    | -2,4    | -3,4  | -6,8          | –         |         |
| Output Voltage: Low-Level, $V_{OL}$ Max.    | –            | 0,5             | 5               | 0,05                                  |           |         |         | –     | 0             | 0,05      | V       |
|   | –            | 0,10            | 10              | 0,05                                  |           |         |         | –     | 0             | 0,05      |         |
|   | –            | 0,15            | 15              | 0,05                                  |           |         |         | –     | 0             | 0,05      |         |
| Output Voltage: High-Level, $V_{OH}$ Min.   | –            | 0,5             | 5               | 4,95                                  |           |         |         | 4,95  | 5             | –         | V       |
|   | –            | 0,10            | 10              | 9,95                                  |           |         |         | 9,95  | 10            | –         |         |
|   | –            | 0,15            | 15              | 14,95                                 |           |         |         | 14,95 | 15            | –         |         |
| Input Low Voltage, $V_{IL}$ Max.            | 4,5          | –               | 5               | 1                                     |           |         |         | –     | –             | 1         | V       |
|   | 9            | –               | 10              | 2                                     |           |         |         | –     | –             | 2         |         |
|   | 13,5         | –               | 15              | 2,5                                   |           |         |         | –     | –             | 2,5       |         |
| Input High Voltage, $V_{IH}$ Min.           | 0,5          | –               | 5               | 4                                     |           |         |         | 4     | –             | –         | V       |
|   | 1            | –               | 10              | 8                                     |           |         |         | 8     | –             | –         |         |
|   | 1,5          | –               | 15              | 12,5                                  |           |         |         | 12,5  | –             | –         |         |
| Input Current $I_{IN}$ Max.                 |              | 0,18            | 18              | $\pm 0,1$                             | $\pm 0,1$ | $\pm 1$ | $\pm 1$ | –     | $\pm 10^{-5}$ | $\pm 0,1$ | $\mu$ A |

# CD4007UB Types

## MAXIMUM RATINGS, Absolute-Maximum Values:

### DC SUPPLY-VOLTAGE RANGE, (V<sub>DD</sub>)

Voltages referenced to V<sub>SS</sub> Terminal ..... -0.5V to +20V

### INPUT VOLTAGE RANGE, ALL INPUTS

..... -0.5V to V<sub>DD</sub> +0.5V

### DC INPUT CURRENT, ANY ONE INPUT

..... ±10mA

### POWER DISSIPATION PER PACKAGE (P<sub>D</sub>):

For T<sub>A</sub> = -55°C to +100°C ..... 500mW

For T<sub>A</sub> = +100°C to +125°C ..... Derate Linearly at 12mW/°C to 200mW

### DEVICE DISSIPATION PER OUTPUT TRANSISTOR

FOR T<sub>A</sub> = FULL PACKAGE-TEMPERATURE RANGE (All Package Types) ..... 100mW

### OPERATING-TEMPERATURE RANGE (T<sub>A</sub>)

..... -55°C to +125°C

### STORAGE TEMPERATURE RANGE (T<sub>stg</sub>)

..... -65°C to +150°C

### LEAD TEMPERATURE (DURING SOLDERING):

At distance 1/16 ± 1/32 inch (1.59 ± 0.79mm) from case for 10s max ..... +265°C

DYNAMIC ELECTRICAL CHARACTERISTICS at T<sub>A</sub> = 25°C; Input t<sub>r</sub>, t<sub>f</sub> = 20 ns, C<sub>L</sub> = 50 pF, R<sub>L</sub> = 200 KΩ

| CHARACTERISTIC          | CONDITIONS       | LIMITS                |      | UNITS |      |
|-------------------------|------------------|-----------------------|------|-------|------|
|                         |                  | V <sub>DD</sub> Volts | Typ. |       | Max. |
| Propagation Delay Time: | t <sub>PHL</sub> | 5                     | 55   | 110   | ns   |
|                         | t <sub>PLH</sub> | 10                    | 30   | 60    |      |
|                         |                  | 15                    | 25   | 50    |      |
| Transition Time         | t <sub>THL</sub> | 5                     | 100  | 200   | ns   |
|                         | t <sub>TLH</sub> | 10                    | 50   | 100   |      |
|                         |                  | 15                    | 40   | 80    |      |
| Input Capacitance       | C <sub>IN</sub>  | Any Input             | 10   | 15    | pF   |





Fig. 1 — Detailed schematic diagram of CD4007UB showing input, output, and parasitic diodes.



(14,2,11); (8,13);  
(1,5); (7,4,9)

92CS-15350



(13,2); (1,11);  
(12,5,8); (7,4,9)


92CS-15349



(1,12,13); (2,14,11);  
(4,8); (5,9)

92CS-15348

### d) Tree (Relay) Logic



(13,12,5); (4,9,8);  
(14,2); (1,11)





Fig. 2 — Sample CMOS logic circuit arrangements using type CD4007UB.


3  
COMMERCIAL CMOS  
HIGH VOLTAGE ICs

# CD4007UB Types


e) High Sink-Current Driver




(6,3,10); (8.5, 12);  
(11,14); (7,4,9)




f) High Source-Current Driver



(6,3,10); (13,1,12);  
(14,2,11); (7,9)




g) High Sink - and Source-Current Driver



(6,3,10); (14,2,11);  
(7,4,9); (13,8,1,5,12)

h) Dual Bi-Directional Transmission Gating



(1,5,12); (2,9);  
(11,4); (8,13,10);  
(6,3)

Fig. 2 - Sample CMOS logic circuit arrangements using type CD4007UB (Cont'd).




Fig. 3 - Typical voltage-transfer characteristics for NAND gate.




Fig. 4 - Typical voltage-transfer characteristics for NOR gate.




Fig. 5 - Typical output low (sink) current characteristics.




Fig. 6 - Minimum and maximum voltage-transfer characteristics for inverter.




Fig. 7 - Typical current and voltage-transfer characteristics for inverter.




Fig. 8 - Minimum output low (sink) current characteristics.

# CD4007UB Types




Fig. 9 - Typical output high (source) current characteristics.




Fig. 10 - Minimum output high (source) current characteristics.




Fig. 11 - Typical voltage-transfer characteristics as a function of temperature.




Fig. 12 - Typical propagation delay time vs. load capacitance.




Fig. 13 - Typical transition time vs. load capacitance.




Fig. 14 - Typical dissipation vs. frequency characteristics.




Fig. 15 - Input current test circuit.




Fig. 16 - Input voltage test circuit.





Fig. 17 - Quiescent device current test circuit.



DIMENSIONS AND PAD LAYOUT FOR CD4007UBH

Dimensions in parentheses are in millimeters and are derived from the basic inch dimensions as indicated. Grid graduations are in mils ( $10^{-3}$  inch).

3  
COMMERCIAL CMOS  
HIGH VOLTAGE ICs

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2)     | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|---------------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| CD4007UBE        | ACTIVE        | PDIP         | N               | 14   | 25          | RoHS & Green        | NIPDAU                               | N / A for Pkg Type   | -55 to 125   | CD4007UBE               | <a href="#">Samples</a> |
| CD4007UBEE4      | ACTIVE        | PDIP         | N               | 14   | 25          | RoHS & Green        | NIPDAU                               | N / A for Pkg Type   | -55 to 125   | CD4007UBE               | <a href="#">Samples</a> |
| CD4007UBF        | ACTIVE        | CDIP         | J               | 14   | 1           | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | CD4007UBF               | <a href="#">Samples</a> |
| CD4007UBF3A      | ACTIVE        | CDIP         | J               | 14   | 1           | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | CD4007UBF3A             | <a href="#">Samples</a> |
| CD4007UBM        | ACTIVE        | SOIC         | D               | 14   | 50          | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -55 to 125   | CD4007UBM               | <a href="#">Samples</a> |
| CD4007UBM96      | ACTIVE        | SOIC         | D               | 14   | 2500        | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -55 to 125   | CD4007UBM               | <a href="#">Samples</a> |
| CD4007UBMT       | ACTIVE        | SOIC         | D               | 14   | 250         | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -55 to 125   | CD4007UBM               | <a href="#">Samples</a> |
| CD4007UBNSR      | ACTIVE        | SO           | NS              | 14   | 2000        | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -55 to 125   | CD4007UB                | <a href="#">Samples</a> |
| CD4007UBNSRG4    | ACTIVE        | SO           | NS              | 14   | 2000        | TBD                 | Call TI                              | Call TI              | -55 to 125   |                         | <a href="#">Samples</a> |
| CD4007UBPW       | ACTIVE        | TSSOP        | PW              | 14   | 90          | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -55 to 125   | CM007UB                 | <a href="#">Samples</a> |
| CD4007UBPWR      | ACTIVE        | TSSOP        | PW              | 14   | 2000        | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -55 to 125   | CM007UB                 | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF CD4007UB, CD4007UB-MIL :**

- Catalog : [CD4007UB](#)
- Military : [CD4007UB-MIL](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

| Device      | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| CD4007UBM96 | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| CD4007UBMT  | SOIC         | D               | 14   | 250  | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| CD4007UBNSR | SO           | NS              | 14   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |
| CD4007UBPWR | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |

**TAPE AND REEL BOX DIMENSIONS**


\*All dimensions are nominal

| Device      | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| CD4007UBM96 | SOIC         | D               | 14   | 2500 | 356.0       | 356.0      | 35.0        |
| CD4007UBMT  | SOIC         | D               | 14   | 250  | 210.0       | 185.0      | 35.0        |
| CD4007UBNSR | SO           | NS              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| CD4007UBPWR | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |



**TUBE**


\*All dimensions are nominal

| Device      | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| CD4007UBE   | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| CD4007UBE   | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| CD4007UBEE4 | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| CD4007UBEE4 | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| CD4007UBM   | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| CD4007BPW   | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

N (R-PDIP-T\*\*)

PLASTIC DUAL-IN-LINE PACKAGE

16 PINS SHOWN



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - $\triangle C$  Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - $\triangle D$  The 20 pin end lead shoulder width is a vendor option, either half or full width.

4040049/E 12/2002

J 14


**GENERIC PACKAGE VIEW**  
**CDIP - 5.08 mm max height**  
CERAMIC DUAL IN LINE PACKAGE



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4040083-5/G

J0014A



**PACKAGE OUTLINE**

**CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE



4214771/A 05/2017

**NOTES:**

1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermetically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
5. Falls within MIL-STD-1835 and GDIP1-T14.

# EXAMPLE BOARD LAYOUT


J0014A

CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE




LAND PATTERN EXAMPLE  
NON-SOLDER MASK DEFINED  
SCALE: 5X



4214771/A 05/2017

D (R-PDSO-G14)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
  - Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
  - E. Reference JEDEC MS-012 variation AB.

D (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4211283-3/E 08/12

- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.



PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4040064-3/G 02/11

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2022, Texas Instruments Incorporated