

AN-2113 Applying I²C Compatible Temperature Sensors in Systems with Slow Clock Edges

ABSTRACT

This Application Note describes a method of interfacing a given microcontroller with a Texas Instruments digital temperature sensor.

Contents

1	Overview	2
---	----------------	---

List of Figures

1	T _{HD, DAT} and T ₃ Definitions	2
2	I ² C Switching Points and Logic Levels	2
3	I ² C Bus Signals	3

1 Overview

Occasionally, there is a question about interfacing a particular microcontroller to one of the Texas Instruments digital temperature sensors. Problems most often occur when the microcontroller has extremely slow falling edges on the clock line, where “extremely slow” means close to the I2C Standard Mode maximum for T_f , or 300ns. When using the Texas Instruments I2C-compatible temperature sensors in your system, keep in mind that only the timing parameters specifically listed in the data sheet are guaranteed. Those data have either been extensively characterized or are tested on each and every part before it leaves the factory. For example, some Texas Instruments digital temperature sensors with Two-Wire Interface do not specify the I2C-Standard timing parameter $t_{HD;DAT}$. T_3 , which is the time for data out to be stable after SCL falls, is the closest specification to $t_{HD;DAT}$ (see Figure 1). There is a footnote in the I2C specification that essentially says the device sending the SDA signal has to wait 300ns before it sends SDA out “to bridge the undefined region of the falling edge of SCL”. Let’s take a look at what the concern is with bridging the undefined region of SCL.




Figure 1. $T_{HD;DAT}$ and T_3 Definitions

Begin by examining the specification for what makes up a logic ‘1’ and what makes up a logic ‘0’ in I²C. Figure 2 shows, as an example, a falling edge of SCL. The region that is assured to be a logic ‘1’ is from 70% of the signal and up to a little bit above the supply. The region that is assured to be a logic ‘0’ is from 30% of the signal down to a little bit below ground. The definition of logic ‘1’ and logic ‘0’ leaves a big part of the signal as undefined: the part from 30% to 70%. This is what the specification refers to when it mentions the undefined region. Due to the difficulty of manufacturing, an input buffer that will have a 30% to 70% hysteresis over all process, temperature and supply, most buffers will actually switch from an input ‘1’ to an input ‘0’ somewhere in the undefined region, although this will not be specified. Therefore, it is not unreasonable to suggest that in a system you could have an input buffer (input A, Figure 2) that has the transition from a ‘0’ to a ‘1’ at the 30% level and another input buffer (input B, Figure 2) that has the transition from a ‘0’ to a ‘1’ at the 70% level. In some cases, this difference in logic transition can cause system problems that are shown in Figure 2.




Figure 2. I²C Switching Points and Logic Levels

The end of a typical bus transaction is shown in Figure 3. In this case, the master has sent information to the slave and the slave sends an ACK back to the master. The master in this example has a very slow fall time on the falling edge of its SCL and SDA signals, on the order of the 300 ns maximum allowed in the specification. The slave ACK bit, however, has a very fast falling edge, on the order of 5 ns, without a 300 ns delay. In most cases, this will not cause problems in the system. However, assume that the master has bus arbitration enabled. In bus arbitration, the master monitors the SCL line and the SDA line as it is sending out information. If the master sees data different from what it sent out, it assumes that another master is attempting to use the bus. At this point, the master typically stops sending data and sets an error

flag to alert the program that it has lost control of the bus. If this happens with only a single master, the system will hang waiting for the bus to be released by another master that doesn't exist. A lost arbitration situation can occur if the SCL input to the slave is like input B, the input to the master that is monitoring the bus is like input A and the fall time of the ACK signal from the slave is much faster than the fall time of the SCL from the master. If those three conditions are met, your master may lose arbitration.




Figure 3. I²C Bus Signals

To determine if your system is at risk for this problem, compare the fall times of the SCL output from the master with the fall times of the slave. There will be two components to the fall time of the ACK: one is the propagation delay through the part (the delay from reading a '0' on SCL to putting out a '0' on SDA) and the other is the actual fall time of the ACK (the 10-90% time). These two components together make up the timing parameter T_3 . The propagation delay is an order of magnitude larger than the fall time in many temperature sensors, so if the fall times are approximately the same (within a few 10s of ns) there will be plenty of margin to avoid unnecessarily losing arbitration. When probing, make sure to follow established probing practices for fast edges to avoid getting erroneous results.

One solution in systems that are having arbitration problems is adding capacitance from the SDA line to ground. That will resolve the problem in all but the most pathological cases. The exact amount of capacitance will depend on the size of the SDA line pull-ups (so as not degrade the rising edge too much), how much capacitance is already on the board and how much capacitance the other devices on the board are able to drive.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com